

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	XFOAM Masking foam tape
CODE	100713 (13 mm)
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

The mask allows masking foam to seal the door, luggage, capes, etc. Preventing the paint from introducing into unwanted places. The foam allows an easy cutting to desired length and size and ensures a proper isolation. The adhesive ensures a successful use without leaving any residue once used.

Strips of adhesive foam roll fuse 50 metres (10 strips of 5 metres). Silicone paper coverage for a total use of the product. Presented in box-dispensed.

3. PROPERTIES

A. Foam

• Features

RESULT	UNIT	REGULATION	SPECIFICATION	
Density	Kg/m ³	UNE-EN ISO 845	28+-2	29.30
Hardness	KPa	UNE-EN ISO 33861	4.5+-0.5	4.08
Def. Remaining	%	UNE-EN ISO1586-A	<5	4.90
Tensile	kPA	DIN 53571	>150	228

B. Adhesive

DESCRIPTION: Adhesive thermo fusible- it melts with heat.

COLOUR/BASE: Transparent/block polymer.

SMELL: Odourless at room temperature.

C. Physical constants of the product (viscosity)

TEMPERATURE	VISCOSITY
180°C	8000+-1000 mPas.
170°C	11000+-1500 mPas.

D. Chemical resistance (*)

- Water: Excellent
- Acids and base: good
- Fats and oils: good
- Aliphatic: Poor
- D. Aromatics: Poor
- D. Alcohols: good

4. STORAGE

It is advisable to store the product in areas with temperatures below 35°C and normal ventilation. Avoid keep the product stored for more than twelve months. Make a good rotation of stock for an optimal result.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.