



F437

#### Features:

Dyed red split welder glove with 15 cm split cuff

Provides good mechanical resistant and comfort

Chromium VI free leather according to EN 420:2003 + A1:2009

## F437

#### Material used

Palm - Dyed red split leather

Back - Dyed red split leather

Cuff - 15 cm cuff

Binding - Synthetic black binding

Liner - Palm lined with cotton cuff lined with canvas

#### Available Size

10

#### Color

Red

#### Specifications:

Liner: Palm lined with cotton cuff lined with canvas

Stitching: 100% Kevlar®

Cuff :15 cm red split cuff

Weight (DZP): 3000 gm



# WELDER GLOVES

*Dyed red leather split welder glove with 15 cm split cuff*



#### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)



## Safe hands!!

### Instruction for use

The glove should not be worn when it exist a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding.

Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100°C).

### Instructions for storage:

➤ Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

➤ Using life depends on character of activity and usage frequency

---

*Mallcom welder gloves provides superior comfort and dexterity with unparallel mechanical resistant properties*

---

### Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

### Instructions for cleaning / maintenance:

It cannot be cleaned

Do not clean in washing machine.

Put the gloves on clean and dry hands.

Check inside and out of gloves before re-use them.

### Packaging Instruction:

36 pairs in a carton



Performance according to EN 388:2003 :

4. Resistance to abrasion (from 0 to 4)
1. Resistance to cut (from 0 to 5)
3. Resistance to tear (from 0 to 4)
3. Resistance to puncture (from 0 to 4)



EN 407 :413X4X

4. Resistance to flammability (from 1 to 4)
1. Resistance to contact heat (from 1 to 4)
3. Resistance to convective heat (from 1 to 4)
- X. Resistance to radiant heat (from 1 to 4)
4. Resistance to small projection from molten metal (from 1 to 4)
- X. Resistance to large projection from molten metal (from 1 to 4)

### Applications:

Welding operation

Hot metal handling

Hot metal sheet processing



**MALLCOM INDIA LTD**

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E: [safety@mallcom.in](mailto:safety@mallcom.in), w: [www.mallcom.in](http://www.mallcom.in)