

600 SERIES

ANNIVERSARY EDITION

Bowers & Wilkins

600 Series Anniversary Edition

603 S2 Anniversary Edition



The powerful 603 S2 Anniversary Edition combines the accuracy and transparency of our acclaimed Continuum mid-range cone with the scale and authority of two dedicated bass drivers. Featuring upgraded crossovers for even more transparency and a unique trim-ring to celebrate its status, the 603 S2 Anniversary Edition is the most sophisticated affordable floor-standing loudspeaker we've ever made.

Technical features	Decoupled Double Dome aluminium tweeter Continuum cone FST™ midrange Paper bass cone Flowport™	
Description	3-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø150mm (6 in) Continuum cone FST midrange 2x ø165mm (6.5 in) Paper bass cone	
Frequency Range	-6dB at 29Hz and 33kHz	
Frequency Response	48Hz - 28kHz ±3dB	
Sensitivity	88.5dB spl (2.83V, 1m)	
Harmonic Distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 22kHz <0.5% 120Hz - 20kHz	
Nominal impedance	8Ω (minimum 3.0Ω)	
Recommended amplifier power	30W - 200W into 8Ω on unclipped programme	
Dimensions	Height: 985mm (38.8 in) cabinet only 1055mm (41.5 in) with plinth Width: 190mm (7.5 in) cabinet only 320mm (12.6 in) with plinth Depth: 340mm (13.4 in) 370mm (14.6 in) with plinth	
Net Weight	24.1kg (53.1 lb)	
Boxed Weight	31.7kg (69.9 lb - single)	
Finishes	Cabinet:	Grille:
	Matte Black	Black
	Matte White	Grey
	Oak	Grey
	Red Cherry	Black





606 S2 Anniversary Edition



The 606 S2 Anniversary Edition is the seventh generation of our iconic 600 Series standmount speaker. The ideal combination of size and power, it blends our advanced Continuum cone with an improved crossover for even more insight in your music. 25 years on, it remains the standard for attainable performance loudspeakers.



Technical features	Decoupled Double Dome aluminium tweeter Continuum cone bass / midrange Flowport™	
Description	2-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø165mm (6.5 in) Continuum cone bass / midrange	
Frequency Range	-6dB at 40Hz and 33kHz	
Frequency Response	52Hz - 28kHz ±3dB	
Sensitivity	88dB spl (2.83Vrms, 1m)	
Harmonic Distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 150Hz - 20kHz	
Nominal impedance	8Ω (minimum 3.7Ω)	
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme	
Dimensions	Height: 345mm (13.5 in) Width: 190mm (7.5 in) Depth: 300mm (11.8 in) cabinet only 324mm (12.8 in) including grille and terminals	
Net Weight	6.9kg (15.2 lb)	
Boxed Weight	16kg (35.3 lb - pair)	
Finishes	Cabinet:	Grille:
	Matte Black	Black
	Matte White	Grey
	Oak	Grey
	Red Cherry	Black




607 S2 Anniversary Edition



Offering power and scale that belies its compact form, the 607 S2 Anniversary Edition features the Continuum cone and updated crossovers to ensure exceptional resolution and musicality. Place them on stands or on a bookshelf for fantastic stereo sound, or use them as rear speakers in a powerful home theatre system.

Technical features	Decoupled Double Dome aluminium tweeter Continuum cone bass / midrange Flowport™	
Description	2-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø130mm (5 in) Continuum cone bass / midrange	
Frequency Range	-6dB at 40Hz and 33kHz	
Frequency Response	52Hz - 28kHz ±3dB	
Sensitivity	84dB spl (2.83V, 1m)	
Harmonic Distortion	2nd and 3rd harmonics (90dB, 1m) <1% 110Hz - 22kHz <0.5% 180Hz - 20kHz	
Nominal impedance	8Ω (minimum 3.0Ω)	
Recommended amplifier power	30W - 100W into 8Ω on unclipped programme	
Dimensions	Height: 300mm (11.8 in)	
	Width: 165mm (6.5 in)	
	Depth: 207mm (8.1 in) cabinet only 231mm (9.1 in) including grille and terminals	
Net Weight	4.7kg (10.4 lb)	
Boxed Weight	11.2kg (24.7 lb - pair)	
Finishes	Cabinet:	Grille:
	Matte Black	Black
	Matte White	Grey
	Oak	Grey
	Red Cherry	Black



HTM6 S2 Anniversary Edition



Powerful enough to partner with 603 S2 Anniversary Edition and compact enough to fit with any piece of furniture, HTM6 S2 Anniversary Edition brings more realism and accuracy to your movie experience.

Technical features	Decoupled Double Dome aluminium tweeter Continuum cone bass / midrange Flowport™
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 2x ø130mm (5 in) Continuum cone bass / midrange
Frequency Range	-6dB at 42Hz and 33kHz
Frequency Response	72Hz - 28kHz ±3dB
Sensitivity	87dB spl (2.83Vrms, 1m)
Harmonic Distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz
Nominal impedance	8Ω (minimum 4.3Ω)
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Dimensions	Height: 160mm (6.3 in) Width: 480mm (18.9 in) Depth: 255mm (10.0 in) cabinet only 279mm (11.0 in) including grille and terminals
Net Weight	7.8kg (17.2 lb)
Boxed Weight	9.2kg (20.3 lb - single)
Finishes	Cabinet: Grille: Matte Black Black Matte White Grey Oak Grey Red Cherry Black

SUBWOOFERS

ASW610XP




This large three-way centre-channel speaker delivers unprecedented power and transparency, for totally convincing voice reproduction. It's designed to be paired with larger speakers in the range, such as the 703 floorstanders.

Technical features

**Dual voice coil drive unit Paper/Aramid
Fibre stiffened cone
500W ICEpower® amplifier**

Description	Active closed-box subwoofer system
Drive units	ø250mm (10 in) paper/Aramid Fibre cone long-throw
Frequency range	-6dB at 18Hz and 25/140Hz adjustable (EQ at A)
Frequency response	±3dB 25Hz – 40/140Hz adjustable (EQ at A)
Bass Extension	-6dB at 18Hz (position A) -6dB at 23Hz (position B) -6dB at 28Hz (position C)
Amplifier	Power output: 500W Rated power Consumption: 94W/0.8W standby Input impedance: 33kΩ Signal / noise: >80dB Functions: Input level (line in) Input level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/ standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Low-pass filter	Active 4th -order, variable cut-off frequency
Dimensions	Height: 325mm (12.8 in) not including feet Width: 325mm (12.8 in) Depth: 374mm (14.7 in) including grille and controls
Net weight	15.5kg (34.4 lb)
Finishes	Cabinet: Black White Grille: Black Light Grey



ASW610



This high performance two-way centre speaker is a great choice for home cinema set-ups in smaller rooms, where space is at a premium. Partner it up with the more compact 700 Series speakers, such as the 706 or the 704.

Technical features

Paper/Aramid Fibre cone drive unit 200W ICEpower® amplifier

Description	Active closed-box subwoofer system
Drive units	ø250mm (10 in) paper/Aramid Fibre cone long-throw
Frequency range	-6dB at 20Hz and 25/140Hz adjustable (EQ at A)
Frequency response	±3dB 27Hz – 40/140Hz adjustable (EQ at A)
Bass Extension	-6dB at 20Hz (position A) -6dB at 25Hz (position B) -6dB at 30Hz (position C)
Amplifier	Power output: 200W Rated power Consumption: 40W/0.5W standby Input impedance: 33kΩ Signal / noise: >90dB Functions: Input level (line in) Input level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Low-pass filter	Active 4th -order, variable cut-off frequency
Dimensions	Height: 310mm (12.2 in) not including feet Width: 310mm (12.2 in) Depth: 375mm (14.8 in) including grille and controls
Net weight	12.5kg (27.6 lb)
Finishes	Cabinet: Black White Grille: Black Light Grey

ASW608



This large three-way centre-channel speaker delivers unprecedented power and transparency, for totally convincing voice reproduction. It's designed to be paired with larger speakers in the range, such as the 703 floorstanders.

Technical features

Paper/Aramid Fibre cone drive unit 200W ICEpower® amplifier

Description	Active closed-box subwoofer system
Drive units	ø200mm (8 in) paper/Aramid Fibre cone long-throw
Frequency range	-6dB at 23Hz and 25/140Hz adjustable (EQ at A)
Frequency response	±3dB 32Hz – 40/140Hz adjustable (EQ at A)
Bass Extension	-6dB at 23Hz (position A) -6dB at 28Hz (position B) -6dB at 36Hz (position C)
Amplifier	Power output: 200W Rated power: Consumption: 40W/0.5W standby Input impedance: 33kΩ Signal / noise: >90dB Functions: Volume level (line in) Volume level (speaker in) Low-pass filter frequency (line in only) Low-pass filter bypass Bass extension Bass roll-off alignment Auto sense on/standby Phase switch Inputs: Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Low-pass filter	Active 4th -order, variable cut-off frequency
Dimensions	Height: 260mm (10.2 in) not including feet Width: 260mm (10.2 in) Depth: 330mm (13 in) including grille and controls
Net weight	8.85kg (19.5 lb)
Finishes	Cabinet: Black White Grille: Black Light Grey





Bowers & Wilkins 600 Series

ANNIVERSARY EDITION

For decades, we have poured our passion for performance and our love of music into everything we do, from our most affordable loudspeakers to our studio-quality 800 Series Diamond range. Now, our 600 Series has turned 25 – an occasion we think is worth celebrating in style.

Introducing the 600 Series Anniversary Edition.
bowerswilkins.com

For the love
of music.





Bowers & Wilkins

www.bowers-wilkins.com
Distributed by Homemation pty.ltd