



RCT 2400 VAS

- **NEW** South African Socket - 2 pin Euro plug compatible
- Power cable included
- Fast charging in 4-6 hours
- Built-in excellent microprocessor controller
- Boost and buck AVR for voltage stabilization
- Free monitoring software download

CAPACITY

2400 VA / 1440 W



INPUT

VOLTAGE:

220 / 230 / 240 VAC

VOLTAGE RANGE:

162 - 290 VAC

FREQUENCY RANGE:

60 / 50 Hz (auto-sensing)

OUTPUT

AC VOLTAGE REGULATION (BATT. MODE):

± 10%

FREQUENCY RANGE (BATT. MODE):

60 Hz or 50 Hz ±1 Hz

TRANSFER TIME:

Typical 2 - 6ms, 10ms max.

WAVE FORM (BATT. MODE):

Simulated Sinewave

BATTERY

BATTERY TYPE & NUMBER:

12 V / 9 AH x 2

TYPICAL RECHARGE TIME:

4 - 6 Hours Recover to 90% Capacity



INDICATORS

AC MODE:

UPS Status LED Lights Up & Top 4 Green LEDs
Gradually Lights Up Indicating Load Level

BATTERY MODE:

UPS Status LED Flashes & Top 4 Green LEDs
Gradually Lights Up Indicating Battery Capacity

FAULT:

Red Lighting

OPERATING ENVIRONMENT

HUMIDITY:

0 - 90% RH @ 0 - 40°C (non-condensing)

NOISE LEVEL:

Less than 40 dB

Please Note: Product specifications are subject to change without further notice.

PRODUCT DIMENSIONS: 397 mm x 146 mm x 205 mm | **PRODUCT WEIGHT:** 13.5kgs

RCT

WWW.RCTZONE.CO.ZA