Rovic Leers	Cape TownTel: +27 (0)21 907 1700PietermaritzburgTel: +27 (0)33 346 2727JohannesburgTel: +27 (0)11 396 6200Rovic AfricaTel: +27 (0)11 396 6240
Incorporating Rovic Africa	admin@rovicleers.co.za albertc@rovicafrica.com www.rovicleers.co.za www.rovicafrica.com
3 POINT - PTO Drive AXIS Double disc (Kuhn) General Characteristics - Very high flow output (500kg/min) - Ultra-slow rotating agitator 17 rpm - Fitted with S6 VXR Fast Fit Disc - Fitted with Hopper sieve	RLS RLS RLS

- Hitch Category 2
- Gearbox 540 rpm
- Fitted with Parking wheels as standardFitted with Mud Flaps
- Hopper cover fitted as standard or Optional



Stock Code	Model	Volume	Extension	Application	Working	GPS	Weighing	Hopper	Border
		Incl Ext.	fitted as std.	rate adj.	width	Control	system	cover	Spreading
UKU1400610	AXIS 30.2 K	2200 L	800L	Manual	24 - 36m	n/a	n/a	Optional	Optional
UKU1400613	AXIS 30.2 Q	3200 L	1800L	DPAE Elect.	24 - 36m	Ready	n/a	Standard	Optional
UKU1400650	AXIS 30.2 W	1400 L	-	DPAE Elect.	24 - 36m	Ready	Standard	Optional	Optional
UKU1400651	AXIS 30.2 W	3200 L	1800L	DPAE Elect.	24 - 36m	Ready	Standard	Standard	Optional

Optional Equipment

opuonai Equip		
KU1409030 Inspection Ladder for 30.1Q and 30.1W (Fitted LH or RH side)		
KU1406435 TELIMAT T25 Border spreading to the right. (Axis 30.2K, 30.2Q, 30.2W)		
KUR4087058 + KUR408	7037 Set S2 VXR Disc (12m- 18m) Exchange with S6 Disc	
KUR4087043 + KUR408	7044 Set S4 VXR Disc (12m- 28m) Exchange with S6 Disc	
KUR4087050 + KUR408	7051 Set S6 VXR Disc (24m- 36m) Fitted as standard	
KUR4087052 + KUR408	7053 Set S8 VXR Disc (30m- 42m) Exchange with S6 Disc	

 Note

 *All weights, measurements & specifications are approximate and subject to change without prior notification.

 * Models listed generally stocked as standard, other models available as special import. (See brochure)