

3-Point Trash Handcult Seedbed Cultivator

Looking for a versatile secondary tillage implement for optimum seedbed preparation and excellent seed emergence?



7.0m Trash Handcult-Folding

"590" Tine Fitted



We have the answer!

- Working widths 2.9, 5.2 and 7.0m.
- Suitable for tractors from 40 to 130 kW.
- NEW range of frames designed for efficiency, good under frame clearance and excellent trash flow (arrowhead tine configuration).
- Mechanical depth wheels for accurate, easy adjustment of working depth.
- Folding wings (hydraulic) on 7.0m model for easy, safe transport.

Choice of Two different tines to fit any frame:

- Unique Rovic "590" Tine, spring reset, breakout force adjustable from 75 to 95 kg.
- Rovic "HD" S-tine: Heavy duty, Coil profile 65x17mm.
- Working depth 175mm.
- Tine spacing 225mm.



"HD" S-Tine



"590" Tine

2.9m and 5.2m Trash Handcult-Rigid



"HD" S-Tine Fitted

Technical Specifications: Rovic 3-Point Mounted Trash Handcult

CHARACTERISTICS	RIGID		FOLDING
	THC - 13T	THC - 23T	THC - 31T
LINKAGE	3-Point (Category 1 & 2)		
WORKING WIDTH *(See optional equipment for other widths)	2.9m	5.2m	7.0m
APPROXIMATE TRACTOR SIZE	40-50kW	65-80kW	95-130kW
NUMBER OF TINES	13	23	31
TRANSPORT WIDTH	3.5m	5.25m	4.68m
CHOICE OF TINES	"590" Spring reset or "HD" S-Tine		
WORKING DEPTH	175mm		
TINE SPACING	225mm		
UNDERFRAME CLEARANCE	570mm		
NUMBER OF RANKS	3	3	4-Centre 3-Wings
HYDRAULIC FOLDING WINGS	n/a	n/a	Standard
DEPTH CONTROL - 600 x 14 MECHANICAL WHEELS	1 x Set	1 x Set	2 x Sets
OPTIONAL EQUIPMENT			
FINGER HARROWS	Optional		
SEEDBED ROLLERS (Medium duty ϕ 258mm slatted)	Optional		
*EXTENSIONS			
ALTERNATE WORKING WIDTHS WITH VARIOUS EXTENSIONS	3.4m / 3.8m	5.6m / 6.0m	7.4m
NUMBER OF TINES WITH VARIOUS EXTENSIONS	15, 17	25, 27	33

All weights, measurements & specifications are approximate and subject to change without prior notification

CHOICE OF TINES

"590" TINE




"HD" S-TINE



OPTIONAL EQUIPMENT

SEEDBED ROLLER



FINGER HARROW

