



Incorporating **RovicAfrica**

Cape Town Tel: +27 (0)21 907 1700
Pietermaritzburg Tel: +27 (0)33 346 2727
Johannesburg Tel: +27 (0)11 396 6200
Rovic Africa Tel: +27 (0)11 396 6240

admin@rovicleers.co.za | albertc@rovicafrica.com
 www.rovicleers.co.za | www.rovicafrica.com

Disc Plough (Rovic)

General Characteristics

- 3-Point mounted Cat. II
- Disc manufactured from Boron Steel / High carbon
- Disc plough angle can be adjusted to suit soil conditions
- Adjustable spring loaded rear Disc coulter to take care of side draft
- Space between Disc \pm 570mm (23")



Stock Code	Model	No. Disc	Disc Specification (mm)	HP required	Width of cut (cm)	Weight (kg)
UBEMDP-2	2 Disc Plough	2	Ø660 x 6	50-60	50-55	\pm 310
UBEMDP-3	3 Disc Plough	3	Ø660 x 6	65-80	875-925	\pm 415
UBEMDP-4	4 Disc Plough	4	Ø660 x 6	85-100	1150-1200	\pm 520
UBEMDP-5	5 Disc Plough	5	Ø660 x 6	105-125	1575-1625	\pm 620
UBEMDP-6	6 Disc Plough	6	Ø660 x 7	130-150	1930-2000	\pm 720

Note

*All weights, measurements & specifications are approximate and subject to change without prior notification.