



## **MT - Rotary Drum Mower**



## MT | Rotary Drum Mower

Rear-mounted drum mower available in two working widths (1.65 mt. and 1.85 mt.). High speed discs allow high quality cutting performances also in stony grounds. Mechanical or hydraulic lifting systems with

cabin control, fast and efficient blades replacement device. Provided with cardan shaft, pulley with over running clutch, protection cover and automatic safety release.



Belt tensioner.



Heavy duty 3 point hitch.



Easy system knives replacement.



Mechanical lifting.



Model	<b>LE</b> Working width	N° Drums	N° knives	©, RPM	HP HP	KG Weight
MT165 M	<b>165</b> cm. 5.5 ft.	2	6	540 rpm	50 HP	<b>360 Kg.</b> 795 Lbs.
MT185 M	185 cm. 6.1 ft.	2	6	540 rpm	75 HP	<b>405 Kg.</b> 895 Lbs.






## **MT - Rotary Drum Mower**



MT | Rotary Drum Mower



MP | 3 Point hitch Hay Rake



MASTER RAKE | Carted V-Rake



MW 200 - 300 | Bale wrappers



MB - MF | Fixed and Side-shift backhoes

SOUTH AFRICA

Cape Town Tel: +27 (0)21 907 1700 Johannesburg Tel: +27 (0)11 396 6200 Pietermaritzburg Tel: +27 (0)33 346 2727

www.rovicleers.co.za **Leading Farming Technology**