

Kuhn - LEXIS 3000L Trailed Boom Sprayer

LEXIS 3000L Trailed Boom Sprayer (Kuhn)



General Characteristics

- 3000 Litre tank capacity
- Polyethylene tank with smooth inside and out
- Dry sight level gauge
- Comet PM 280 Piston-diaphragm pump
- Retractable Parking stand
- Adjustable drawbar height
- Large platform with rails
- Pressure gauge
- Hydraulic agitation
- Large suction filter
- 320L Rinse tank, 20L clean water tank
- 3 rotating rinse nozzles
- 35L chemical inductor with can rinse
- Track adjustable axle 1.5 to 2.25m
- 5m Filling hose with filter (CAMLOCK Coupling)
- Road lights
- Wheel size 13.6 x 38
- No parking brake
- 2 x Storage Locker

Boom specification:

24m MEA2 Aluminium boom	
<ul style="list-style-type: none"> - EQUILIBRA Suspension (Pendulum with yaw dampening system plus Automatic contour following) - Hydraulic slanting - Stainless steel boom tubes - 4 way nozzle holders with anti-drip - In line filter for each section - Electric controlled ball section valves - Nozzle height; from 0.5m to 2.5m 	
Low specification	High specification
<ul style="list-style-type: none"> a) RPB control (DPAE) Constant at varying speeds by pressure b) 4 Spray sections c) Hydraulic simultaneous opening in one step (LH and RH together) d) 3 Function selector (1x SA + 1x DA) 	<ul style="list-style-type: none"> a) REB 3 Controller (DPAE) Constant at varying speeds by flow b) 7 Spray sections c) Hydraulic Individual fold d) Opening in 3 steps (24/12) e) CH 10 Hydraulic Box - Independent LH and RH boom tilt

Part no.	Description	Tyre	Boom
ULE3000/24	Lexis - 3000L tank c/w 24m boom (Low spec)	13.6 x 38	24m (Alum)
ULE3000/24H	Lexis - 3000L tank c/w 24m boom (High Specification)	13.6 x 38	24m (Alum)

Optional Equipment

	Tyre and Rim 9.5 x R48 (Vegetable Wheel) In Lieu of standard (13.6 x 38) Fitted at Rovic Leers	
ULEVEG	Tyre and Rim 9.5 x R48 (Vegetable Wheel)	Each
ULESTD	Tyre and Rim 13.6 X 38 (Standard Wheel, Broad Acre)	Each
ULEMG480	480mm Mud Guard Set	Set