

# MINI-CLIK™

Sensor: **Rain, Freeze**

*This sensor halts scheduled irrigation when it detects a preset level of rain has fallen to stop water waste.*

## KEY BENEFITS

- Shuts off irrigation automatically when the sensor detects rainfall from 3 mm to 19 mm
- Debris tolerant for reliable operation and no unnecessary shutdowns
- Compatible with most normally open or normally closed irrigation controllers

## OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 3 A
- Includes 7 m of 0.5 mm<sup>2</sup> sheathed, UL-approved wire
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

## USER-INSTALLED OPTIONS

- Optional Gutter Mount (P/N SGM)



**Mini-Clik Sensor**  
(with mounting arm)  
Height: 5 cm  
Length: 15 cm  
Width: 2.5 cm



**Mini-Clik Sensor**  
(with stainless steel enclosure)  
Height: 13.9 cm  
Length: 7.6 cm  
Width: 10.1 cm

MINI-CLIK	
Model	Description
MINI-CLIK	Mini-Clik Sensor
MINI-CLIK-NO	Mini-Clik Sensor, normally open switch
MINI-CLIK-C	Mini-Clik Sensor, conduit mount
SG-MC	Mini-Clik Sensor in a stainless steel sensor enclosure

Compatible with:



**Waterproof Wire Connector**