



Incorporating **RovicAfrica**

Cape Town Tel: +27 (0)21 907 1700
Pietermaritzburg Tel: +27 (0)33 346 2727
Johannesburg Tel: +27 (0)11 396 6200
Rovic Africa Tel: +27 (0)11 396 6240

admin@rovicleers.co.za | albertc@rovicafrica.com
 www.rovicleers.co.za | www.rovicafrica.com

SIDE DISCHARGE, Trailed Manure & Slurry Spreader (Kuhn)



General Characteristics

- Patented twin Auger design
- L.H. Hammer discharge with free swinging forged hammers
- Spreads the widest variety of materials: Solid and semi-liquid manure, bedding material, sand, compost etc.
- Hydraulically adjusted deflector to control spread width and height
- Axles: SL 110 Single axle
 SL 114 Tandem Oscillating axle

	SL 110	SL 114
Overall width	2.5m	2.6m
Overall length	5.5m	6.12m

	SL 110	SL 114
Overall height	1.7m	1.88m
w/o Splash Guard	1.5m	1.65m

Stock Code	Model	Capacity (Struck)	Discharge	Max. Net pay load	Min kW	PTO Speed	Axle & Tyres
UKN188110TV	SL 110 Orchard	3.80m ³	Horizontal	4,082 kg	45kW	540 rpm	Single (10.5 / 80)
UKN188114T	SL 114 Broad acre	4.05m ³	Slinger	5,443 kg	66kW	540 rpm	Tandem (14 / 16.1)

Note

- *All weights, measurements & specifications are approximate and subject to change without prior notification.
- * Models listed generally stocked as standard, other models available as special import. (See brochure)