

Conservation Tillage Soil Aeration: Super 25 & 32 Deep Ripper Implements



INTRODUCING 650mm & 800mm WORKING DEPTHS

- Super 25: 650mm working depth
- Super 32: 800mm working depth
- The tines are manufactured from best quality steel to ensure optimal strength under the toughest conditions.
- DOUBLE leaf spring trip action (no shearbolts!), break out force up to a massive 1500kg!
- Specially designed to work in sandy soils with deep plough banks, the unique tine shape allows easy penetration in even the toughest soils
- Super-tough frames to match the tines! Frames manufactured from imported, hot rolled high tensile steel, the best money can buy!
- Tine spacing 400, 500 or 600mm
- 3-point model frames with 5, 7, 9 or 11 tines
- Rip-On-The-Row frames with tines grouped in sets of 2 or 3 at row intervals of 1,5m or 2,3m
- Trailed 15 & 17 tine frames

Super 25
Deep Ripper



650mm

– Up to 650mm
working depth



Super 32
Deep Ripper



800mm

– Up to 800mm
working depth

DOUBLE leaf spring trip action (no shearbolts!)



Technical Specifications: Super 25 & 32 Deep Ripper Implements

CHARACTERISTICS	3-Point Mounted		Rip-on-the-row		Trailed	
	5-7	9-11 M400 9-13 M600	1.5m	2.3m	15 Tine	17 Tine
ATTACHMENT	3-Point: Category 3 & 4		3-Point: Category 3 & 4		Trailed	
TUBING	160 x 160 square		160 x 160 square		160 x 160 square	
NUMBER OF TINES	5 or 7	9 / 11 / 13	10 / 15 / 18	6 or 9	15	17
TINE SPACING	400-500mm	400mm	1.5m	2.3m	500mm	500mm
TINE SETS	n/a	n/a	5 sets 2t = 10t 5 sets 3t = 15t 6 sets 3t = 18t	3 sets 2t = 6t 3 sets 3t = 9t	n/a	n/a
NUMBER OF RAMMS	2		2		2	
FRAME CONFIGURATION	Rigid		Rigid		Folding	
APPROXIMATE TRACTOR SIZE: SUPER 25 TINE	150-210kW	270-390kW	300-450kW	160-270kW	450kW	510kW
APPROXIMATE TRACTOR SIZE: SUPER 32 TINE	200-280kW	340-520kW	400-600kW	240-360kW	600kW	680kW
WORKING DEPTH: SUPER 25 TINE	650mm		650mm		650mm	
WORKING DEPTH: SUPER 32 TINE	800mm		800mm		800mm	
UNDER FRAME CLEARANCE: SUPER 25	850mm		850mm		850mm	
UNDER FRAME CLEARANCE: SUPER 32	1050mm		1050mm		1050mm	
DEPTH CONTROL	11L x 15 mechanical wheels	14.5 / 80-18 mechanical, adjustable wheels	14.5 / 80-18 mechanical, adjustable wheels	mechanical, adjustable wheels	400 / 60 - 22.5 mechanical adjustable wheels	
OPTIONAL EQUIPMENT						
HEAVY DUTY CRUMBLE ROLLERS (Ø450mm)	Optional		Optional		Optional	
CHOICE OF TINES	Super 25 or 32		Super 25 or 32		Super 25 or 32	

All weights, measurements & specifications are approximate and subject to change without prior notification

SOUTH AFRICA

Cape Town Tel: +27 (0)21 907 1700
 Johannesburg Tel: +27 (0)11 395 6200
 Pietermaritzburg Tel: +27 (0)33 346 27 27

www.rovicleers.co.za
 Leading Farming Technology

CHOICE OF TINES



OPTIONAL EQUIPMENT

