

Rovic Spreads Value with : Trailed Belt Spreaders

Belt Cassette



RF4500 Belt Spreader



RF3000 Belt Spreader



RF2000 Belt Spreader



RF2000 SPREADER with banding chute

Belt Cassette:

- Ideally suited to spread **Granular Fertilizer and Lime**
- Conveyor cassette - Land wheel drive (DPA)
- Sieve fitted as standard
- Hydraulic clutch to disengage gearbox drive to conveyor cassette
- GPS compatible
- Twin disc spinner (PTO drive)
- 3 Models available:
 - **RF2000 - 2 000 L Orchard**
 - **RF3000 - 3 000L**
 - **RF4500 - 4 500L**



Benefits for you

- **Constant application per hectare**, even with varying ground speeds
- **Easy conversion to GPS**, and Vice Versa
- **Allows for low application rate** - down to 50kg/ha for granular fertilizer and high application rates – up to 3 tons/ha for lime
- Spreads **Lime up to 12m** and **Fertilizer up to 18m**
- **Suited for most tractors**, even for tractors with only one hydraulic port and/or low hydraulic flow rate
- **Sieve to filter foreign objects, breaks up material** to be spread

SPECIFICATIONS : BELT	RF2000 Belt	RF3000 Belt	RF4500 Belt
Volume - Struck	1900L	2900L	4500L
Volume - Heaped	2200L	3300L	5100L
Spread width - Granular Fertilizer (depending on density & pallet size)	up to 12m	up to 18m	up to 18m
Spread width - Lime (depending on density)	8 to 10m	8 to 12m	8 to 12m
Belt width	500mm	500mm	800mm
Maximum net pay load	2600kg	4000kg	6100kg
Dimensions width / length / height with sieve (m)	1.4 / 4.05 / 1.57 m	1.97 / 4.1 / 2.05 m	2 / 5 / 2.3 m

All weights, measurements & specifications are approximate and subject to change without prior notification



Scan this QR code and subscribe to the Rovic Leers newsletter

Leading Farming Technology

Rovic Spreads Value with : Trailed Chain Spreaders

Chain Cassette



RL4500 Chain Spreader



RL10000 Chain Spreader

Chain Cassette:

- Ideally suited to spread **Lime and Dry Manure**
- Conveyor cassette - Land wheel drive (DPA)
- Sieve fitted as standard
- Hydraulic clutch to disengage wheel drive-chain to conveyor cassette
- GPS compatible
- Twin disc spinner (Variable hydraulic drive)
- 2 Models available:

- **RL4500 - 4 500L**
- **RL10000 - 10 000L**



Benefits for you

- **Constant application per hectare**, even with varying ground speeds
- **Easy conversion to GPS**, and Vice Versa
- **Ability to deliver material** that is lumpy and difficult to transport
- **Great traveling speed** between paddocks
- Spreads **Lime up to 12m** and **Organic Material up to 18m**
- **Spinner speed and spread-pattern** can easily be set to meet material requirements.
- **Short turning circle**

SPECIFICATIONS : CHAIN

	RL4500 Chain	RL10000 Chain
Volume - Struck	4500L	10000L
Volume - Heaped	5100L	10700L
Spread width - Lime (depending on density)	8 to 12m	8 to 12m
Spread width - Dry Manure (depending on type)	up to 18m	up to 18m
Chain width	850mm	1000mm
Maximum net pay load	6100kg	12800kg
Dimensions width / length / height with sieve (m)	2.5/ 5.3 / 2.65 m	2.88/ 7.08 / 2.85 m

All weights, measurements & specifications are approximate and subject to change without prior notification

SOUTH AFRICA

Cape Town Tel: +27 (0)21 907 1700
 Johannesburg Tel: +27 (0)11 396 6200
 Pietermaritzburg Tel: +27 (0)33 346 27 27

www.rovicleers.co.za

