

**TRAILED Vertical Feeder Mixer Wagon (Seko)**

**VML200 - Standard Equipment**

- 2 x Vertical chopping mixing augers fitted with toothed blades
- 2 x Hydraulically operated counter blades
- SK400 Weighing system with 15 recipes
- R.H. Front Discharge Conveyor 0.9m (w) x 1.4m (L)
- Epicycloidal gear-box with two speed gear
- Product containment ring
- Adjustable drawbar with Ø45mm towing eye
- Mechanical support foot
- Inspection ladder with platform
- Capacity expressed in m<sup>3</sup> applies to products of specific weight max. 350kg/m<sup>3</sup>



Illustration not representative of the model imported as

Stock Code	Model	Min kW	Control	Capacity m <sup>3</sup> / Ton	Axle	Wheels	Conveyor R.H. Front	Vertical Augers	Counter Blades (Hydraulic)
SEK-VML140	Tiger VML140	66kW	Electric	14m <sup>3</sup> / 4.9t	Single	19/45 R17.0	1.4m (Chain)	x 2	x 2
SEK-VML160	Tiger VML160	74kW	Electric	16m <sup>3</sup> / 5.6t	Single	19/45 R17.0	1.4m (Chain)	x 2	x 2
SEK-VML200	Tiger VML200	81kW	Electric	20m <sup>3</sup> / 7t	Single	445/45 R19.5	1.4m (Chain)	x 2	x 2

**Other models available as special import, please enquire**

- \* Trailed for tractor coupling (7m<sup>3</sup> - 45m<sup>3</sup>)
- \* Self Propelled (12m<sup>3</sup> - 33m<sup>3</sup>)
- \* Stationery units (9m<sup>3</sup> - 45m<sup>3</sup>)

**Note**

- \*All weights, measurements & specifications are approximate and subject to change without prior notification.
- \* Models listed generally stocked as standard, other models available as special import. (See brochure)