

## BTT

Take advantage of smartphone-controlled, above-ground irrigation for easier access to the hose tap.

### Key Benefits

#### Number of zones:

- 1 or 2
- 1 smartphone manages an unlimited number of controllers
- Cycling mode repeats continuously within user-defined water windows, perfect for drip systems or germinating seeds
- Manual push-button operation for quick operation without a smartphone
- Blinking LED low-battery alert indicates battery replacement
- Alkaline batteries included for quicker installation
- Battery-operated tap timer with Bluetooth® control
- 1-second to 24-hour run time with 4 start times
- Suspend irrigation up to 99 days during the off-season, perfect for seasonal markets
- Automatic water shutoff after 1 hour prevents water waste
- Secure passcode protection prevents unauthorised schedule changes
- Includes quick coupler adapter

### OPERATING SPECIFICATIONS

- Two 1.5V AA alkaline batteries (included)
- Flow rate: 1.9 to 2,271 L/H
- Approvals: Plastic IPX6, UL, cUL, FCC, CE, RCM
- Recommended pressure: 0.5 to 8 bar (50 to 800 kPa)
- Bluetooth 5.0 (BLE)
- Warranty period: 2 years

### APP Specifications

- iOS® 9.0 or above
- Maximum communication distance: 10 m
- Android™ 4.4 or above



Number of Stations: 1 or 2  
Type: **Battery Operated, Fixed Bluetooth App Control**



**BTT-101**  
Outlet Diameter: ¾"  
Inlet Diameter: ¾" and 1"  
Height: 16.8 cm  
Width: 12 cm  
Depth: 6 cm



**BTT-201**  
Outlet Diameter: ¾"  
Inlet Diameter: ¾" and 1"  
Height: 15.7 cm  
Width: 13.5 cm  
Depth: 7.6 cm



**BTT-LOC (Optional)**  
Outlet Diameter: 16-18 mm Drip Tube  
Inlet Diameter: ¾"  
Height: 7 cm  
Width: 3 cm



**Pressure Regulator (Optional)**  
Outlet Diameter: ¾"  
Inlet Diameter: ¾"  
Height: 7 cm  
Width: 4 cm

Model	Description
BTT-101	1-zone Bluetooth Tap Timer, 1" BSP and 3/4" hose thread, quick coupler adapter
BTT-201	2-zone Bluetooth Tap Timer, 1" BSP and 3/4" hose thread, quick coupler adapter
BTT-LOC	BTT adapter for 16-18 mm dripline

### Pressure Regulator Models:

Model	Description
PRLG203FH3MH	1.4 bar (138 kPa) pressure regulator, 3/4" hose thread
PRLG253FH3MH	1.7 bar (172 kPa) pressure regulator, 3/4" hose thread
PRLG303FH3MH	2 bar (207 kPa) pressure regulator, 3/4" hose thread
PRLG403FH3MH	2.8 bar (276 kPa) pressure regulator, 3/4" hose thread