

ECO LOGIC

The reliable Eco Logic Controller is the first choice for small residential areas and has the option for water-saving accessories.

KEY BENEFITS

- Number of stations:
 - 4 or 6 (fixed models)
- 2 programs with 4 start times each, and up to 4-hour run times
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Suspend irrigation up to 7 days during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Seasonal adjustment for quicker schedule adjustments without changing run times

OPERATING SPECIFICATIONS

- Transformer input: 230 VAC
- Transformer output (24 VAC): 0.625 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals: UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

ECO LOGIC

Model	Description
ELC-401i-E	4-station indoor controller, 230 VAC wall adapter
ELC-601i-E	6-station indoor controller, 230 VAC wall adapter



Plastic Indoor

Height: 12.6 cm
Width: 12.6 cm
Length: 3.2 cm

Compatible with:



Soil-Clik
Sensor



Wind-Clik
Sensor

ECO LOGIC

