



CAPE TOWN +27 (0)21 907 1700
admin@rovicleers.co.za

JOHANNESBURG +27 (0)11 396 6200
infojhb@rovicleers.co.za

PIETERMARITZBURG +27(0) 33 346 2727
infopmb@rovicleers.co.za

Kuhn - Mounted Gyrotedders

<i>Kuhn - Mounted Gyrotedders</i>							
Characteristics	GF 422	*GF 502	GF 582	GF 642	GF 5202	GF 5902	GF 6502
3-Point Attachment	Category 1 & 2			Category 2			
DIN working width	4.2m	5.0m	5.75m	6.4m	5.2m	5.9m	6.5m
Number of rotors	4		6		4		6
Number of tines per rotor	6		5	6	7	5	6
Pivoting head stock	as standard						
Oblique position setting	by manual wheel positioning				centralized		
Rotors driven by the exclusive "Digidrive" system	as standard						
Tyres	balloon tyres 15 x 6.00 - 6				balloon tyres 16 x 6.50 - 8		
Width in transport position	2.50m	2.85m	2.4m	2.95m	2.99m	2.53m	2.99m
Transport height	2.37m	2.72m	2.95m	3.3m	2.8m	3.01m	3.29m
Putting into transport position	hydraulic vertical fold						
PTO power requirement kw	15kW		20kW	22kW	15kW	20kW	22kW
Protection	PTO with slip clutch				PTO with torque limiter		
Weight	470kg	505kg	690kg	840kg	660kg	810kg	920kg
Necessary tractor hydraulic equipment	1 x SA valve		1 x DA valve	1 x SA valve	1 x DA valve		1 x SA valve
Lighting and signalling	-	-	-	standard	standard	-	standard

*General specifications on model imported to S.A. (All other models available as special import, please enquire)

Please note:

All weights, measurements & specifications are approximate and subject to change without prior notification.