

PRO-C®

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

Key Benefits

Number of stations:

- Modular Pro-C: Conventional wiring from 4 to 23 stations, Two-wire EZ Decoder option up to 32 stations
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
- Easy Retrieve™ memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ provides simple diagnostics of faulty field wiring

Electrical Specifications

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years



Number of Stations: 4-32
Type: Fixed and Modular



Plastic Indoor

Height: 23 cm
Width: 25 cm
Depth: 12 cm



Plastic Outdoor

Height: 23 cm
Width: 25 cm
Depth: 12 cm



Modular Expansion

Pro-C's Modular version allows easy expansion after initial installation

PC-Series Station Expansion Models:

Model	Description
PCM-300	3-Station plug-in module: Use to increase station count from 4 to 7, 7 to 10, and 10 to 13
PCM-900	9-Station plug-in module: Use to increase station count from 7 to 16 only
PCM-1600	16-station plug-in module
PC-DM	EZ Decoder output module
PCM-1600-KIT	Upgrade kit for 16-station plug-in module
PC-DM-KIT	Upgrade kit for EZ decoder output module
EZ-1	Single-station decoder with status LED

Compatible Sensors

SOLAR-SYNC-SEN	Solar Sync sensor and wire.
WSS-SEN	Wireless Solar Sync sensor and receiver.
RAIN-CLIK	Wired Rain-Clik sensor
WR-CLIK	Wireless Rain-Clik. Includes sensor and receiver
MINI-CLIK	Rain Sensor
FREEZE-CLIK	Freeze sensor interrupts irrigation when temperatures drop below 3°C (37° F)
WIND-CLIK	Wind sensor interrupts/returns irrigation when programmed wind speed is measured
FLOW-CLIK	Standard kit for all 24 VAC controllers. Includes sensor and interface module, sensor requires FCT for pipe installation.
SOIL-CLIK	Soil-Clik moisture sensor module and probe

PRO-C® - SPECIFICATION BUILDER

1 Model	2 Indoor/Outdoor	3 Transformer	4 Option
PC-4 4-station base module controller	(blank) Outdoor model (<i>internal transformer</i>)	00 120 VAC	(blank) No option
	i Indoor model (<i>plug-in transformer</i>)	01 230 VAC	E 230 VAC with European connections
			A 230 VAC with Australian connections (<i>outdoor models have internal transformer with cord</i>)