



Incorporating **RovicAfrica**

**Cape Town** Tel: +27 (0)21 907 1700  
**Pietermaritzburg** Tel: +27 (0)33 346 2727  
**Johannesburg** Tel: +27 (0)11 396 6200  
**Rovic Africa** Tel: +27 (0)11 396 6240

admin@rovicleers.co.za | albertc@rovicafrica.com  
 www.rovicleers.co.za | www.rovicafrica.com

## ÄÖ - Q-Series Parallel Lift Loaders (45kW > 149kW)

*Note! Specially designed for Heavy Duty / Arduous work of up to 2000 cycle hrs per year*

Characteristics	Q-series			
	Q4-S	Q5-S	Q6-M	Q7-M
Working cycle (Hours per year)	up to 2000 hrs per year			
Intensity	Heavy / Arduous (eg. Silage / Contracting)			
Max Lift height (Under level implement)	± 3.49m	±3.76m	± 3.95m	± 4.3m
Max. Lift capacity (80cm from Pivot point)	1,920kg	1,980kg	2,470kg	2,490kg
*Rated for tractors	60 - 105kW	75 - 180kW	90 - 165kW	105 - 208kW
Quick hitch tool carrier (Euro one)	Standard			
Parallel Lift	Standard			
Hydraulic operation	Remote Joy-stick (cable) c/w Multi-coupler			
Sub-Frame	Drive-in type			
Grill Guard	Standard			
* <i>Note! The model loader relevant to tractor size (kW) is merely indicative. For correct pairing please submit the make and model tractor to your nearest Rovic Leers Branch and request that they confirm the model loader suggested will fit your tractor.</i>				



**Q-Series**  
(45 - >120kW)

Specification	Other Dimension Loader models available as special import											
	Q3-S	Q3-M	Q3-L	Q4-M	Q4-L	Q5-M	Q5-L	Q6-S	Q6-L	Q7-S	Q7-L	Q8-M
Max Lift height under level impl.	3.25m	3.25m	3.51m	3.49m	3.72m	3.76m	3.90m	3.95m	4.25m	4.3m	4.45m	4.66m
Max. Lift cap. (80cm from Pivot point)	1,550kg	1,850kg	1,740kg	2,260kg	1,780kg	2,300kg	1,930kg	2,140kg	1,980kg	2,170kg	2,490kg	2,590kg
Rated for tractors	45 - 75kW	45 - 75kW	45 - 75kW	60 - 105kW	60 - 105kW	75 - 135kW	75 - 135kW	90 - 165kW	90 - 165kW	105 - 208kW	105 - 208kW	> 120kW

### Optional equipment

- 1.) Selecto 3 - 3<sup>rd</sup> Function (Required for attachment that works with hydraulic cylinder)
- 2.) Selecto 4 - 4<sup>th</sup> Function (Requires 3<sup>rd</sup> Function)
- 3.) Soft Drive - Shock absorber. Q3 to Q4-L (Electric ON / OFF)
- 4.) Soft Drive - Shock absorber. Q5 to Q8-M (Electric ON / OFF)
- 5.) EasyDrive LCS hydraulic kit with 'Electronic' operation (Basic function)
- 6.) Electrodrive LCS professional hydr. kit with 'Electronic' operation (Multiple function)
- 7.) Q-Series Loader Light for improved visibility when working in the dark (Set of two lights)
- 8.) Q-Companion integrated support system (Load weighing, status monitor & maintenance reminder)



**Q-Companion - Integrated driver support system for NEW Q-Series Loaders**  
 Enables; Status Monitoring, Load weighing and Maintenance reminding



**Note!**

- Can be Retro or Factory fitted (Stand alone)
- Must be installed In-Cab (Not suited for tractors without cab)

**Note**

- \*All weights, measurements & specifications are approximate and subject to change without prior notification.
- \* Models listed generally stocked as standard, other models available as special import. (See brochure)