

KUHN - Mower Conditioners

Trailed MOWER CONDITIONERS (Kuhn)

General characteristics:

- Individual removable disc bearing station
- PROTECTADRIVE Gear train protection system
- GYRODINE Headstock



● Rubber conditioning Rollers

Stock code	Model	No. Disc	Hitch Semi-mount	Drawbar	Conditioning	Min kW	PTO speed (rpm)	Blade attach
UFC2860TLR	FC 2860 TLR	6	Cat. 2 or 3	Side	Rubber Rollers	48kW	540	Fast-Fit
UFC302R	FC 302 RG	6	Cat. 2 or 3	Side	Rubber Rollers	52kW	540 or 1000	Bolted
UFC352RG	FC 352 RG	7	Cat. 2 or 3	Side	Rubber Rollers	66kW	540 or 1000	Bolted
UFC3560TLR	FC 3560 TLR	8	Cat. 2 or 3	Side	Rubber Rollers	62kW	1000	Fast-Fit
UFC3560TCR	FC 3560 TCR	8	Cat. 2 or 3	Central	Rubber Rollers	62kW	1000	Fast-Fit
UFC4060TCR	FC 4060 TCR	9	Cat. 2 or 3	Central	Rubber Rollers	69kW	1000	Fast-Fit

● Steel conditioning Rollers

UFC3560TCS	FC 3560 TCS	8	Cat. 2 or 3	Central	Steel Rollers (x2)	62kW	1000	Fast-Fit
UFC4060TCS	FC 4060 TCS	9	Cat. 2 or 3	Central	Steel Rollers (x2)	69kW	1000	Fast-Fit
UFC4460TCS	FC 4460 TCS	10	Cat. 2 or 3	Central	Steel Rollers (x2)	76kW	1000	Fast-Fit

● Steel conditioning Fingers

UFC3160TLD	FC 3160 TLD	7	Cat. 2 or 3	Side	Steel Fingers	55kW	1000	Fast-Fit
UFC3560TLD	FC 3560 TLD	8	Cat. 2 or 3	Side	Steel Fingers	62kW	1000	Fast-Fit
UFC3560TCD	FC 3560 TCD	7	Cat. 2 or 3	Central	Steel Fingers	62kW	1000	Fast-Fit

Optional equipment

KU1066310	Raised Skid Set (Adjust. From 55 - 150mm) Standard on FC 302RG / 352RG	Require one set per machine
-----------	--	-----------------------------