

ÄlÖ - VERSA-X Parallel Lift Loaders (± 29kW - 90kW)

Note! Specially designed for Medium Duty utility farm work of up to 500 cycle hrs per year

Characteristics	Versa X			
	X26	X36	X46	X56
Working cycle (Hours per year)	Up to 500 hrs per year			
Intensity	General day to day material handling			
Max Lift height (Under level implement)	±2.9m	± 3.2m	± 3.5m	± 3.7m
Max. Lift capacity (80cm from Pivot point)	1,220kg	1,520kg	1,590kg	1,680kg
*Rated for tractors	29-44kW	37 - 51kW	44 - 61kW	51 - 90kW
Quick hitch tool carrier (Euro one)	Standard			
Parallel Lift	Standard			
Hydraulic operation	Remote Joy-stick (cable) c/w Multi-coupler			
Sub-Frame	Drive-in type			
Grill Guard	Optional			

** Note! The model loader relevant to tractor size (kW) is merely indicative. For correct pairing please submit the make and model tractor to your nearest Rovic Leers Branch and request that they confirm the model loader suggested will fit your tractor.*



Note!

1.) The Versa X range of front end loader has specially been designed for Medium Duty Utility farm work of up to 500 cycle hours per year and not intended to be used for Heavy / Arduous Silage handling and contract work. (The Dimension range has been designed for Heavy / Arduous Silage handling and contract work.

Optional equipment

- 1.) 3rd Function (Required for attachment that works with hydraulic cylinder)
- 2.) Soft Drive shock absorber (Manual ON / OFF)
- 3.) Multi Coupler hydraulic connection
- 4.) Grill Guard

Note

*All weights, measurements & specifications are approximate and subject to change without prior notification.
* Models listed generally stocked as standard, other models available as special import. (See brochure)