






CABLE CONNECTOR, NON-INSULATED

Circular Plug Sleeves/Circular Plugs

* for Single-Wire Seals

Illustration	mm ²	Insul. dia. in mm	Seal dia. in mm	Pin dia. in mm	Locking lug	Material	Surface	Art. No.	P. Qty.
	0.5 - 1.0	1.4 - 2.3	3.40	3.5	2 x	CuSn	Sn (tinned)	0558 990 001 *	100
	1.5 - 2.5	2.1 - 3.1	3.40	3.5	2 x	CuSn	Sn (tinned)	0558 990 002 *	100
	1.5 - 2.5	-	-	3.5	2 x	CuSn	Sn (tinned)	0558 990 1	100
	2.1 - 5.3	-	-	3.5	2 x	CuZn	Sn (tinned)	0558 997 7	100
	1.5 - 2.5	-	-	3.5	2 x	CuSn	Sn (tinned)	0558 990 2	100
	4.0 - 6.0	-	-	3.5	2 x	CuSn	Sn (tinned)	0558 990 4	100
	0.5 - 2.0	-	-	3.5	2 x	CuSn	Ag (silver-plated)	0558 990 201	100
	1.5 - 2.5	-	-	3.5	2 x	CuSn	Ag (silver-plated)	0558 990 203	100
	4.0 - 6.0	-	-	3.5	2 x	CuCrSiTi	Ag (silver-plated)	0558 990 204	100

Can be stored in ORSY® system





Additional products – recommendation:

Releasing Tool

Releasing Tool

Art. No. 0713 558 160

Art. No. 0558 991 4..

Illustration	mm ²	Pin dia. in mm	Locking lug	Material	Surface	Art. No.	P./Qty.
	0.5 - 1.0	2.1	1 x	CuZn	Sn (tinned)	0558 996 8	100
	1.0 - 2.5	2.1	1 x	CuZn	Sn (tinned)	0558 990 5	100
	1.0 - 2.5	2.1	1 x	CuZn	Sn (tinned)	0558 990 6	100
	0.5 - 1.5	2.1	2 x	CuZn	Sn (tinned)	0558 993 1	100
	0.5 - 1.5	2.1	2 x	CuZn	Sn (tinned)	0558 993 2	100

Can be stored in ORSY® system







Additional products – recommendation:

Releasing Tool

Releasing Tool for Art. No. 0558 990 6

Art. No. 0713 558 130

Art. No. 0713 558 110

Illustration	mm ²	Pin dia. in mm	Locking lug	Material	Surface	Art. No.	P./Qty
	0.75 - 1.5	1.65	3 x	CuSn	Sn (tinned)	0558 996 81	100
	0.75 - 1.5	1.65	3 x	CuSn	Sn (tinned)	0558 990 77	100
	0.5 - 1.0	1.65	3 x	CuSn	Sn (tinned)	0558 990 8	100
	1.5 - 2.5	1.65	3 x	CuSn	Sn (tinned)	0558 996 61	100
	0.5 - 1.0	1.65	3 x	CuSn	Sn (tinned)	0558 990 7	100
	0.5 - 1.0	1.65	4 x	CuSn	Sn (tinned)	0558 996 4	100
	0.5 - 1.0	1.65	4 x	CuSn	Sn (tinned)	0558 997 0	100
	1.5 - 2.5	1.65	4 x	CuSn	Sn (tinned)	0558 997 1	100

Can be stored in ORSY® system

Additional products – recommendation:




Releasing Tool

Releasing Tool

for Art. No. 0558 990 7/ 0558 990 77/ 0558 996 81

Art. No. 0713 558 130

Art. No. 0713 558 140

Illustration	mm ²	Pin dia. in mm	Material	Surface	Art. No.	P./Qty
	0.5 - 1.5	4.0	CuZn	Sn (tinned)	0558 190 29	100
	0.5 - 1.0	4.0	CuZn	bare	0558 930	100
	1.5 - 2.5	4.0	CuZn	bare	0558 505 1	100
	0.5 - 1.0	4.0	CuZn	bare	0558 503 8	100
	1.5 - 2.5	4.0	CuZn	bare	0558 513 3	100

Can be stored in ORSY® system