

AUTOMOTIVE FINE-SANDING DISK



Base	Foam/grid fabric
Bond	All-synthetic resin
Grain	Aluminum oxide
Scattering	Special process
Color on grain side	50 mm dia.: black, 75 and 150 mm dia.: dark blue
Available grits	500, 1,000, 2,000, 3,000, 4,000
Forms	Washers

Diameter	Adhesion sys.	Sanding pattern	Art. No.	P.Qty.
50 mm	Hook-and-loop	1,000	0587 400 100	25
50 mm	Hook-and-loop	2,000	0587 400 200	25
50 mm	Hook-and-loop	4,000	0587 400 400	25
75 mm	Hook-and-loop	2,000	0587 841 200	20
75 mm	Hook-and-loop	3,000	0587 841 300	20
150 mm	Hook-and-loop	500	0587 843 050	20
150 mm	Hook-and-loop	1,000	0587 843 100	20
150 mm	Hook-and-loop	2,000	0587 843 200	20
150 mm	Hook-and-loop	3,000	0587 843 300	20

Instructions

Ideal for wet and dry sanding.

For the removal of dust inclusions, paint runs, orange peeling, fine sanding before polishing and matting of paint surfaces.

Considerably shorter sanding and polishing times

Outstanding removal power with up to six times the sanding power.

Full-surface extraction

Thanks to the foam-grid fabric, sanding dust is extracted thoroughly and over the whole surface, resulting in an even sanding pattern.

Pressure compensating, absorbent and permeable

The homogeneity of the foam guarantees a controlled absorption and emission of water.

Safe working

The foam prevents pressure from being concentrated at any one point on the surface, which reduces the risk of sanding through at edges, depressions and curves to a minimum.