

INFORMATION ON COMPASS SAW BLADES

Material	Mount	Quality	Art. No.	P. Qty.	Image	Type						
							Tooth pitch in mm	Total length in mm	L. teeth in mm	Thickness in mm		
Metal	Single cam-shank (T-shank) suitable for: Würth STP, AEG, Atlas Copco, Bosch, DeWalt/Elu, Festool, Hilti, Hitachi, Kress, Holz-Her, Makita, Metabo and Skil	***	0608 116 123	1=5		HSS progressive	1.2-2.6	100	75	1.0		
			0608 116 124	1=25								
			0615 050 12	1=5								
			0615 050 15	1=5								
			0615 050 20	1=5								
		**	0608 913 123	1=5		Bi-metal milled, corrugated	1.2	132	108	1.0		
			0608 116 104	1=5			HSS sharpened and conically ground	2.5	100	75	1.25	
			*	0608 116 007	1=5			HSS wavy	0.7	91	66	1.0
				0608 115 93	1=5				1.1-1.5	91	66	1.0
				0608 116 006	1=5				1.9-2.3	91	66	1.0
	0608 115 94	1=5			1.1-1.5	91	66		1.0			
	Würth SP/fine	**	0615 150 12	1=5		Bi-metal corrugated	1.2	88	63	1.0		
			0615 150 20	1=5			2.0	88	63	1.0		
		*	0608 116 088	1=5		HSS wavy	0.7	80	63	1.0		
			0608 116 082	1=5			1.2	88	63	1.0		
			0608 116 083	1=5			2.0	80	63	1.0		
			0608 116 087	1=5			1.0	132	100	1.0		
			0608 116 085	1=5			3.0	100	75	1.0		

¹ = especially for curved sawing