

## BS 14-A COMPACT BATTERY-OPERATED DRIVER DRILL



### Properties:

Ease of handling:	●●●○
Endurance:	●●●●
Power:	●●○○

**Lightweight, powerful lithium ion battery-powered driver drill for all medium-heavy tightening and drilling tasks.**

**With two 14.4 V batteries, charger and fully equipped bit box in case.**

**Art. No. 5700 400 2**

**In case, without charging unit and rechargeable batteries.**

**Art. No. 5700 400 01**

**Very compact and ergonomic design with low weight and belt clip.**

For pleasant, low-fatigue working.

**With 4.0 Ah lithium-ion battery packs**

Long running time per battery charge. The practical battery charge indicator provides information at all times on the energy reserves still available.

**Four-pole motor**

Similar to 4-wheel drive, better distribution of force than with ordinary two-pole motor.

**Overload protection**

Prevents damage to motor and battery caused by overloading.

**LED lamp on battery base**

The working area is always well lit. No shadows are caused by chuck.

**3-year guarantee**

On manufacturing and material defects.

Scope of delivery			
Designation	Art. No.	P. Qty. Art. No. 5700 400 2	P. Qty. Art. No. 5700 400 01
BS 14-A Compact Battery-Operated Driver Drill	<b>5700 400 X</b>	1	1
LI CV 14.4 V/4.0 Ah Battery	<b>0700 916 432</b>	2	-
AL 30-CV-LI Quick Charging Unit	<b>0700 816</b>	1	-
Bit Box, Empty	<b>0614 250 110</b>	1	-
Bit Holder with Quick-Change Chuck	<b>0614 176 711</b>	1	-
2 x AW20, 2 x AW30, 2 x PZ2, PZ3, PH2 Bits	<b>0614 ...</b>	1	-
Case Insert	<b>5800 400 995</b>	1	1
ORSY 200 Empty Case	<b>0955 702 1</b>	1	1

Technical Data		
Voltage	14.4 V	
Battery capacity	4.0 Ah	
Idling speed in 1st/2nd gear	0-500/1,600 rpm	
Max. torque (soft/hard screwing situation)	25/60 Nm	
Max. screw dia.	7 mm	
Max. drilling diameter in	Steel	13 mm
	Wood	32 mm
Chuck clamping range	1.5-13 mm	
Dimensions (Length x Height)	185 x 248 mm	
Weight incl. battery	1.7 kg	

**Available in the fleet management system ORSY®fleet.**