

PNEUMATIC HOSE WINDER DSA-S



<STEPREF A="AT_Picture-Caption" AR="ASSET_

Practical safety hose winder with high-quality polyurethane hose for order and safety in the workplace.

Safe and comfortable work

The hose is guided from left to right while being wound up, preventing knots. The brake function minimises the risk of the hose being flung around in an uncontrolled manner if it is inadvertently released.

Protection against pollution

The robust, enclosed plastic housing protects the hose and the rolling mechanism from dust and other contaminants.

High resistance to kinking with an extremely low weight as well as resistance to oils and solvents. Excellent behaviour in low and high temperature ranges.

High-quality polyurethane hose (PUR)

No pressure drop for more efficiency and cost savings

Hose has a high flow capacity as well as an innovative connection valve on the reel unit

Can be mounted on the wall, ceiling or floor

Bracket ensures a secure attachment to straight surfaces.

Low maintenance costs

Hose can be replaced without opening the housing.

Supply-hose length	1.5 m
Hose length (from stopper ball)	25 cm

Art. No.	0699 080 11	0699 080 18	0699 095 17	0699 130 8
P. Qty.	1	1	1	1
Version	With R 1/4 inch external thread	With R 1/4 inch external thread	With R 3/8 inch external thread	With R 1/2 inch external thread
Hose length	11 m	18 m	17 m	8 m
Inner hose diameter	8 mm	8 mm	9.5 mm	13 mm
Max. pressure	16 bar	16 bar	16 bar	10 bar