

## BASIC VIDEO ENDOSCOPE



**With 5.5 mm x 1 m, semi-rigid probe, 7 parts**

**Quick and easy visual inspection of damage in awkward places without costly and time-intensive disassembly work (e.g. sills, engine, transmission, axles, cavities, cable ducts and many other applications)**

**Art. No. 0715 53 962**

P. Qty.: 1 piece

| Delivery Scope                                    |                    |         |
|---|--------------------|---------|
| Designation                                       | Art. No.           | P. Qty. |
| Endoscope probe 5.5 mm - 1 m semi-rigid 0 degrees | <b>0715 53 776</b> | 1       |
| Mirror attachment, 70 degrees x 5.5 mm            | <b>0715 53 973</b> |         |
| Mirror attachment, 90 degrees x 5.5 mm            | <b>0715 53 974</b> |         |
| Mirror attachment, 110 degrees x 5.5 mm           | <b>0715 53 976</b> |         |
| Hook attachment, 5.5 mm                           | <b>0715 53 972</b> |         |
| Magnet attachment, 5.5 mm                         | <b>0715 53 971</b> |         |
| Manual unit                                       | -                  |         |
| AV cable  | -                  | 4       |
| Alkaline battery AA 1.5 V                         | -                  |         |
| Plastic carrying case                             | -                  | 1       |

| Accessories                                       |                    |         |
|---|--------------------|---------|
| Designation                                       | Art. No.           | P. Qty. |
| Endoscope probe 5.5 mm - 1 m Flex 0 degrees       | <b>0715 53 762</b> | 1       |
| Endoscope probe 3.9 mm - 1 m semi-rigid 0 degrees | <b>0715 53 775</b> |         |
| Endoscope probe 5.5 mm - 3 m Flex 0 degrees       | <b>0715 53 777</b> |         |
| Endoscope probe 5.5 mm - 10 m Flex 0 degrees      | <b>0715 53 778</b> |         |
| Adapter for probe 5.5 mm - metall for type 3 in 1 | <b>0715 53 956</b> |         |
| Adapter for probe 5.5 mm - plastic for type Hazet | <b>0715 53 957</b> |         |

### Technical data:

- 2,4" TFT LCD QVGA color monitor (resolution: 320 x 240 pixels)
- Weight: 1,704 grammes/set
- Video output format: NTSC & PAL
- Viewing angle: Horizontal angle 46°  
Vertical angle 34°  
Diagonal angle 56°
- Depth of focus (DOF): between 1-6 cm distance
- Probes: water-resistant in acc. with Protection Class IP 67

- 4 powerful & dimmable mini LEDs.
- Portable system independent of the mains
- Direct connection possibility with AV socket and connecting cable
- Probes with scratchproof sapphire glass for a high image quality and to protect the camera and lens
- Various mirrors for the widest possible viewing angle
- Digital zoom function and image reflection

**Additional article:**

**Alkaline battery AA 1,5 V**

**Art. No. 0827 112**