

POLYESTER FABRIC ADHESIVE TAPE



Excellent ageing and chemical resistance

- Abrasion and tear resistant
- PVC-compatible

Application area

For bundling and bandaging cable harnesses, especially where high temperatures can occur (e.g. in the engine compartment)

Art. No.	0771 100 119
P. Qty.	1
Width	19 mm
Thickness	0.27 mm
Min./max. temperature resistance	-40 to 150 °C
Length	25 m
Colour	Black
Min. longitudinal resistance to tearing	200 N/cm
Elongation at break	20 %
Backing material	Polyester
Adhesive base	Acrylate

POLYESTER FLEECE ADHESIVE TAPE



Dampens noise

- High adhesive strength
- Ageing-resistant
- PVC-compatible
- Solvent-free

Application area

For bundling and bandaging cable harnesses, especially with padded windings, as an alternative to foam and felt tapes when insulating and damping properties are required, and as noise, rattle and abrasion protection (e.g. in the instrument panel, vehicle interior etc.)

Art. No.	0771 100 219
P. Qty.	1
Width	19 mm
Thickness	0.50 mm
Min./max. temperature resistance	-40 to 105 °C
Length	10 m
Colour	Black
Min. longitudinal resistance to tearing	30 N/cm
Elongation at break	10 %
Backing material	Woven polyester fleece
Adhesive base	Synthetic rubber

The usage instructions are recommendations based on the tests we have conducted and based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.