

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SILICONE SPECIAL 250 RED - 70 ML  
Product code : 0890321

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Sealant  
stance/Mixture : Professional use product

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
  
Telephone : +49 794015 0  
  
Telefax : +49 794015 10 00  
  
E-mail address of person : prodsafe@wuerth.com  
responsible for the SDS

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**  
Not a hazardous substance or mixture.

#### Additional Labelling

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

None known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Triacetoxymethylsilane	17689-77-9 241-677-4	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 3 - < 5
Substances with a workplace exposure limit :			
Manganese ferrite black spinel	68186-94-7 269-056-3		>= 10 - < 20

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

---

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Metal oxides  
Carbon oxides  
Silicon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents
- Storage class (TRGS 510) : 11, Combustible Solids
- Storage period : 12 Months
- Recommended storage temperature : 20 °C

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Manganese ferrite black spinel	68186-94-7	AGW (Inhalable fraction)	0,2 mg/m <sup>3</sup> (Manganese)	DE TRGS 900
Peak-limit: excur-	8;(II)			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

Exposure factor (category)				
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., The threshold value is based on the element content of the corresponding metal., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	0,02 mg/m <sup>3</sup> (Manganese)	DE TRGS 900
Peak-limit: excursion factor (category)	8;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., The threshold value is based on the element content of the corresponding metal., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		TWA (inhalable fraction)	0,2 mg/m <sup>3</sup> (Manganese)	2017/164/EU
Further information	Indicative			
		TWA (Respirable fraction)	0,05 mg/m <sup>3</sup> (Manganese)	2017/164/EU
Further information	Indicative			
Silicon, amorphous	112945-52-5	AGW (Inhalable fraction)	4 mg/m <sup>3</sup> (Silica)	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, sili-cagel)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetic acid	64-19-7	AGW	10 ppm 25 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		TWA	10 ppm 25 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			
		STEL	20 ppm 50 mg/m <sup>3</sup>	2017/164/EU
Further information	Indicative			

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

Substance name	End Use	Exposure routes	Potential health effects	Value
Manganese ferrite black spinel	Workers	Inhalation	Long-term local effects	10 mg/m <sup>3</sup>
Triacetoxyethylsilane	Workers	Inhalation	Long-term local effects	32,5 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	32,5 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	6,5 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Triacetoxyethylsilane	Fresh water	0,2 mg/l
	Marine water	0,02 mg/l
	Intermittent use/release	1,7 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	0,74 mg/kg
	Marine sediment	0,074 mg/kg
	Soil	0,031 mg/kg

## 8.2 Exposure controls

### Engineering measures

Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

Eye protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Wear the following personal protective equipment:  
Safety glasses

Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Equipment should conform to DIN EN 166

### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : >= 0,5 mm  
Directive : DIN EN 374

Material : Chloroprene  
Break through time : > 480 min  
Glove thickness : >= 0,5 mm  
Directive : DIN EN 374

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : >= 0,5 mm  
Directive : DIN EN 374

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

- 
- |                          |   |   |
|--------------------------|---|---|
| Remarks                  | : | Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |
| Skin and body protection | : | Skin should be washed after contact.  |
| Respiratory protection   | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to DIN EN 133  |
| Filter type              | : | Combined particulates and organic vapour type (A-P)   |

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- |  |   |   |
|--|---|---|
| Appearance                                       | : | paste                                   |
| Colour   | : | coloured                                |
| Odour  | : | stinging                                |
| Odour Threshold                                  | : | No data available                       |
| pH   | : | No data available                       |
| Melting point/freezing point                     | : | No data available                       |
| Initial boiling point and boiling range          | : | No data available                       |
| Flash point                                      | : | Not applicable                          |
| Evaporation rate                                 | : | Not applicable                          |
| Flammability (solid, gas)                        | : | Not classified as a flammability hazard |
| Upper explosion limit / Upper flammability limit | : | No data available                       |
| Lower explosion limit / Lower flammability limit | : | No data available                       |
| Vapour pressure                                  | : | Not applicable                          |
| Relative vapour density                          | : | Not applicable                          |
| Relative density                                 | : | No data available                       |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

---

Density	:	1,09 - 1,11 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	ca. 400 °C
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size	:	No data available
---------------	---	-------------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

### 10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

### 10.6 Hazardous decomposition products

Contact with water or humid air	:	Acetic acid
---------------------------------	---	-------------

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

---

Information on likely routes of exposure : Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg  
Method: Expert judgement

#### Components:

##### **Triacetoxymethylsilane:**

Acute oral toxicity : LD50 (Rat): 1.460 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

##### **Manganese ferrite black spinel:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### Components:

##### **Triacetoxymethylsilane:**

Species : Rabbit  
Result : Corrosive after 3 minutes to 1 hour of exposure

##### **Manganese ferrite black spinel:**

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Product:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version  
3.11

Revision Date:  
14.06.2019

SDS Number:  
429870-00004

Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

---

### Components:

#### **Triacetoxymethylsilane:**

Result : Irreversible effects on the eye

#### **Manganese ferrite black spinel:**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **Triacetoxymethylsilane:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

Assessment : Does not cause skin sensitisation.

#### **Manganese ferrite black spinel:**

Test Type : Maurer optimisation test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Triacetoxymethylsilane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

#### **Manganese ferrite black spinel:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

---

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### Manganese ferrite black spinel:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

### Repeated dose toxicity

### Components:

#### Manganese ferrite black spinel:

Species : Rat  
NOAEL : 10,1 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412  
Remarks : Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

### Components:

#### Triacetoxylethylsilane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 251 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 168,7 mg/l  
Exposure time: 48 h  
Remarks: Data from similar compositions

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 24,41 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 18 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

---

Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Manganese ferrite black spinel:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100.000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

## 12.2 Persistence and degradability

### **Components:**

#### **Triacetoxymethylsilane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 74 %  
Exposure time: 21 d

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

Not relevant

## 12.6 Other adverse effects

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version 3.11      Revision Date: 14.06.2019      SDS Number: 429870-00004      Date of last issue: 23.04.2019  
Date of first issue: 11.06.2010

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product, unused product  
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
- uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances
- Acc. Packaging Ordinance properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.
- 

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Dibutylbis[(1-oxodecyl)oxy]stannane (Number on list 20)
- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable
- Water contaminating class (Germany) : WGK 1 slightly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)
- Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0 %

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

- Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

### Full text of H-Statements

H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Eye Dam. : Serious eye damage  
Skin Corr. : Skin corrosion  
2017/164/EU : Commission Directive (EU) 2017/164 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
2017/164/EU / STEL : Short term exposure limit  
2017/164/EU / TWA : Limit Value - eight hours  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## SILICONE SPECIAL 250 RED - 70 ML

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2019
3.11	14.06.2019	429870-00004	Date of first issue: 11.06.2010

---

Sheet cy, <http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN