

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CYLINDER LOCK SPRAY - 50 ML  
Product code : 0893052

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Corrosion inhibitor  
Professional use product

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
  
Telephone : +49 794015 0  
  
Telefax : +49 794015 10 00  
  
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification



#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1      H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.  
  
Skin irritation, Category 2      H315: Causes skin irritation.  
  
Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.

### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Additional Labelling

EUH208 Contains 2,6-Di-tert-butyl-4-nonylphenol. May produce an allergic reaction.

### 2.3 Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
n-Hexane	110-54-3 203-777-6 601-037-00-0	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,25 - < 1
2,6-Di-tert-butyl-4-nonylphenol	4306-88-1 224-320-7	Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,1 - < 0,25

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

		H410	
		M-Factor (Acute aquatic toxicity): 1	
		M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
  
May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |   |
|-------------------------|---|---|
| Technical measures      | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation | : | Use with local exhaust ventilation.<br>Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential   |
| Advice on safe handling | : | Do not get on skin or clothing.<br>Do not breathe vapours or spray mist.<br>Do not swallow.<br>Avoid contact with eyes.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep away from heat and sources of ignition.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br><br>Do not spray on an open flame or other ignition source. |
| Hygiene measures        | : | Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.  |

### 7.2 Conditions for safe storage, including any incompatibilities

- |   |   |  |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage                      | : | Do not store with the following product types:   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

Recommended storage temperature : 10 - 30 °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned	AGW	700 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dan-			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

	gerous substances, See also No. 2.9 of the TRGS 900			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	2006/15/EC
Further information	Indicative			
		AGW	50 ppm 180 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	8;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
n-Hexane	110-54-3	2,5-hexanedione plus 4,5-dihydroxy-2-hexanone: 5 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Hexane	Workers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	75 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	5,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	16 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg bw/day
2,6-Di-tert-butyl-4-nonylphenol	Workers	Inhalation	Long-term systemic effects	7,84 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic	1,11 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	1,93 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	0,56 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,056 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Oral (Secondary Poisoning)	9,33 mg/kg food
2,6-Di-tert-butyl-4-nonylphenol	Fresh water	0,124 µg/l
	Freshwater - intermittent	1,24 µg/l
	Marine water	0,012 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	106 mg/kg dry weight (d.w.)
	Marine sediment	10,6 mg/kg dry weight (d.w.)
	Soil	21,1 mg/kg dry weight (d.w.)

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Use with local exhaust ventilation.

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Equipment should conform to DIN EN 166

### Hand protection

Material : Nitrile rubber  
Break through time : < 480 min  
Glove thickness : 0,45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing, unless as-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

assessment demonstrates that the risk of explosive atmospheres or flash fires is low.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Equipment should conform to DIN EN 133

Filter type : Self-contained breathing apparatus

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Propellant : Isobutane, Propane, Butane

Colour : red brown

Odour : bitter almond

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : -12 °C  
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 11 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 0,83 g/cm<sup>3</sup> (20 °C)

Solubility(ies)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure	:	Inhalation Skin contact Ingestion
--	---	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Eye contact

### Acute toxicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,61 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

#### n-Hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31,86 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### 2,6-Di-tert-butyl-4-nonylphenol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

#### n-Hexane:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### **2,6-Di-tert-butyl-4-nonylphenol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation

#### **n-Hexane:**

Species : Rabbit  
Result : No eye irritation

### **2,6-Di-tert-butyl-4-nonylphenol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

#### **n-Hexane:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

### **2,6-Di-tert-butyl-4-nonylphenol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OPPTS 870.5395  
Result: negative

#### **n-Hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

#### **2,6-Di-tert-butyl-4-nonylphenol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Method: OECD Test Guideline 476  
Result: negative

Test Type: in vitro micronucleus test  
Method: OECD Test Guideline 487  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

#### **n-Hexane:**

Species : Mouse  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Method : OECD Test Guideline 451  
Result : negative  
Remarks : Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

#### **n-Hexane:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Application Route: inhalation (vapour)  
Result: positive

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: inhalation (vapour)  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **2,6-Di-tert-butyl-4-nonylphenol:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

### **STOT - single exposure**

Not classified based on available information.

#### **Components:**

### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

### **n-Hexane:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

#### **Components:**

### **n-Hexane:**

Exposure routes : inhalation (vapour)  
Target Organs : Central nervous system  
Assessment : May cause damage to organs through prolonged or repeated exposure.

### **2,6-Di-tert-butyl-4-nonylphenol:**

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### **Repeated dose toxicity**

#### **Components:**

### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

### **n-Hexane:**

Species : Mouse  
LOAEL : 1,76 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks

Species : Rat, male  
NOAEL : 568 mg/kg  
LOAEL : 3.973 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### **2,6-Di-tert-butyl-4-nonylphenol:**

Species : Rat  
LOAEL : 100 mg/kg  
Application Route : Ingestion  
Exposure time : 63 Days  
Method : OECD Test Guideline 422

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **n-Hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### **Experience with human exposure**

#### **Components:**

#### **n-Hexane:**

Inhalation : Target Organs: Central nervous system  
Symptoms: Central nervous system depression

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8,2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,5 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 0,5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,6 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **n-Hexane:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,5 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,88 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOEL (Pseudokirchneriella subcapitata (green algae)): 30 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **2,6-Di-tert-butyl-4-nonylphenol:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,124 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,007 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): > 0,007 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77,05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **n-Hexane:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **2,6-Di-tert-butyl-4-nonylphenol:**

Biodegradability : Result: Not inherently biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302C

### 12.3 Bioaccumulative potential

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

Partition coefficient: n-octanol/water : log Pow: 4  
Remarks: Based on data from similar materials

### n-Hexane:

Partition coefficient: n-octanol/water : log Pow: 4

### 2,6-Di-tert-butyl-4-nonylphenol:

Partition coefficient: n-octanol/water : log Pow: > 6,5

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

unused product  
16 05 04, gases in pressure containers (including halons) containing hazardous substances

used product  
16 05 04, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

### SECTION 14: Transport information

#### 14.1 UN number

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

#### 14.2 UN proper shipping name

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

#### 14.3 Transport hazard class(es)

**ADN** : 2  
**ADR** : 2  
**RID** : 2  
**IMDG** : 2.1  
**IATA** : 2.1

#### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

### IATA (Cargo)

Packing instruction (cargo aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

---

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Water contaminating class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 47,9 %, 344,62 g/l  
Remarks: VOC content excluding water

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version 8.3      Revision Date: 04.03.2019      SDS Number: 526816-00002      Date of last issue: 04.02.2019  
Date of first issue: 11.06.2010

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H336 : May cause drowsiness or dizziness.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2006/15/EC : Europe. Indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : TRGS 903 - Biological limit values  
2006/15/EC / TWA : Limit Value - eight hours  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## CYLINDER LOCK SPRAY - 50 ML

Version	Revision Date:	SDS Number:	Date of last issue: 04.02.2019
8.3	04.03.2019	526816-00002	Date of first issue: 11.06.2010

---

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN