

# TECHNICAL DATA SHEET

**0893 105 8**

## Wire cable spray

High-quality protective wax with OMC 2 technology for lubricating and preserving

### Fields of application:

For universal use on winches, lifts, conveying and lifting systems and support and attachment cables

### Properties:

- Sprayable corrosion protection wax
- Wear prevention additives
- Does not drip with heat development
- Optimum creeping capacity
- Outstanding resistance to water
- Contains additives with OMC 2 technology
- Silicone and AOX-free
- Resin and acid-free
- Free from solid lubricants
- Compatible with Viton and Perbunan elastomers
- Weather-resistant

### Application:

Thoroughly clean parts using brake cleaner and spray evenly.  
Repeat application provides a thick protective film.

### Technical data:

<b>Base</b>	<b>Synthetic wax oxidate</b>
Colour	Brown
Water resistance (DIN 51807 T1)	0 - 90
Corrosion protection (DIN 51802)*	No rust spots after 7 cycles
Temperature range	-40°C to 120°C
Density at 20°C (active substance)	0.775g/ml

\*1 cycle = 1 week = 168 hrs.

# **TECHNICAL DATA SHEET**

We provide this information to advise you to the best of our knowledge based on our tests and experience. However, due to the large number of applications and the storage and handling conditions that lie outside the scope of our influence, we assume no liability for the application results in individual cases.

This also applies to the use of the non-binding technical and commercial customer services provided by us. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and to further develop our products.