

# TECHNICAL DATA SHEET

## 0893 188 silk matt, 0893 188 1 high-gloss

### Clear varnish

Colourless protective varnish for painting over untreated wood surfaces. For universal use, fast-drying 1C clear varnish with excellent polishing properties and excellent surface appearance.

### Fields of application:

Recommended for touch up work and varnishing components. Solvent or water-based varnishes and sanded old varnishes are suitable surfaces.

### Properties:

- Quick drying
- Compatible with all AC and NC varnishes

### Application:

Shake can vigorously for at least two minutes. When coating entire surfaces for the first time, spray the surface evenly with a back-and-forth motion while maintaining a distance of 20–30 cm.

### Technical data:

Odour	Characteristic
Ignition temperature	365 °C
Vapour pressure	3600 hPa at 20 °C
Water solubility	Can be partially mixed
Shelf life	24 months

### Notes:

The two clear varnishes are not suitable for synthetic resin lacquers. Turn the can over after use and spray until the valve is empty. An adhesion agent must be used first on varnishable plastics. On account of the large number of plastics, we recommend conducting spray test beforehand.

# TECHNICAL DATA SHEET

This advice is based on our own research and experience. It is presented in good faith and may be considered reliable. However, due to the diverse processing, application and handling possibilities the information provided may not be considered legally binding. The same applies to the information provided by our technical and commercial customer service.

We recommend the users of our products to perform their own tests in order to determine whether our products are appropriate for the respective use and environment. We guarantee the consistent quality of our products. We reserve the right to implement technical changes and improvements.