

TECHNICAL DATA SHEET

0890 403 201;
0890 403 202;
0890 403 203;
0890 403 204;
0890 403 205;
0890 403 206;
0890 403 207;
0890 403 208;
0890 403 209;
0890 403 210;

0890 403 211;
0890 403 212;
0890 403 213;
0890 403 214;
0890 403 215;
0890 403 216;
0890 403 217;
0890 403 218;
0890 403 219;
0890 403 220;

0890 403 235;
0890 403 236;
0890 403 237;
0890 403 239;
0890 403 240;
0890 403 241;
0964 890 4;
0964 890 430;

Soft Wax – Brown Colour Assortment

Fields of application:

Especially suitable for many types of soft wood. For filling veneer cracks, lengthwise and lateral scratches, holes, dents, small cracks and scratches, and small open joints not subject to greater loads such as cabinet sides, backs or doors.

Properties:

- Large selection of colours for a wide range of different wood colour tones
- Highly economical, as inexpensive repair works replace expensive treatment of the entire surface
- Easy application
- Colour tones can be intermixed

Application:

Remove crumbly and splintered parts and clean damaged rims. If necessary, adjust basic colour tone for lighter tones in advance. Extract wax with a plastic plane (art no. 0890 305 30) and treat damaged area. Remove excessive wax with plastic plane. Important: Plane with rounded grooves for edges and soft woods and sharp grooves for surfaces.

TECHNICAL DATA SHEET

Seal with clear varnish (art. no. 0893 188 2 / 0893 188 3) afterwards. Trail the wood grain with touching-up materials and restore pore pattern. Finally, spray clear varnish on the treated area (spraying distance 30 – 40 cm) to protect the area from dust and dirt and to seal it.

Technical data:

Basis	Wax
Colours	Pure White (0890 403 201) Colourless, light (0890 403 202) Natural Maple (0890 403 203) Pine (0890 403 204) Maple, Red-Medium (0890 403 205) Medium Beech (0890 403 206) Sen Ash (0890 403 207) Medium Alder (0890 403 208) Dark Beech (0890 403 209) Light Oak (0890 403 210) Medium Cherrywood (0890 403 211) Medium Pearwood (0890 403 212) Dark Pearwood (0890 403 213) Rustic Oak (0890 403 214) Dark Oak (0890 403 215) Brown (0890 403 216) Medium Walnut (0890 403 217) Brown Mahogany ((0890 403 218) Bog Oak (0890 403 219) Jet Black (0890 403 220) Brown Oak (0890 403 235) Chestnut (0890 403 236) Rosewood (0890 403 237) Dark Walnut (0890 403 239) Antique Walnut (0890 403 240) Dark Mahogany (0890 403 241)

TECHNICAL DATA SHEET

Softening point according to ISO 2207	66 °C
Drop point according to DIN 51801	74 °C
Processing time	2 to 3 minutes
Flash point	>80 °C
Water solubility	Insoluble
Disposal	No special disposal regulations have to be followed. Can be disposed of with household garbage.
Shelf life	without any limit in the original closed container and at room temperature

Remarks:

Please note that wood has a natural colour which is dependent on various factors (e.g. origin, exact type of tree, surface treatment etc.). Therefore, an inconspicuous touch-up can never be carried out with a single wax colour.

This advice is based on our own research and experience. It is presented in good faith and may be considered reliable. However, due to the diverse processing, application and handling possibilities the information provided may not be considered legally binding. The same applies to the information provided by our technical and commercial customer service.

We recommend the users of our products to perform their own tests in order to determine whether our products are appropriate for the respective use and environment. We guarantee the consistent quality of our products. We reserve the right to implement technical changes and improvements.