



- * EnergySaving function 1: Default is all fans automatically activated if system temperature up to 38 degree-C
- * EnergySaving function 2: Default is 38 degree-C but individual fan can be adjusted between 30~60 degree-C
- * EnergySaving function 3: Four fan fail display and alert (stop warning by any button)
- * EnergySaving function 4: Device can be switched to Celsius or Fahrenheit Degree (push C/F button)
- * Drive space: 2x5.25" ODD (max. 160mm deep), 4x2.5" SSD (max. 15mm high), 2x3.5" HDD (anti-vibration)
- * The main sheet metal constructed by 1.2mm~2.0mm SECC thickness mechanism
- * Standard with two USB 2.0 ports and LAN/HDD/Power LED at front bezel (two USB 3.0 as option)
- * Standard with multi-functional design by 2U rackmount, and desktop platform
- * Standard equipped with Removable dust filter & quick assembly expansion card holder
- * Build in one brand new 80mmx25mm intake fan behind the front air filter (fan part# D80SM-12)
- * Compatible MB: Mini-ITX 6.7"x6.7" (170mm x 170mm), chassis depth at 250mm only
- * Support standard 1U FlexATX 250W~600W power supply (maximum power depth: 150mm)
- * Support 1 slot full high expansion card via optional riser card (max. 175mm deep)
- * Standard paint: scratch-resistant black textured at front side of chassis
- * IPC China chassis with all build-in electronics in global 3 years warranty
- * Chassis dimension: 19" x 2U x 250mm (9.84" deep)
- * Accessory: #6 round screw x17, M3 truss screw x7, M3 countersunk screw x16
- * Package: NW 4.5 KG, GW 5.5 KG, 1.34 CUFT (carton size at 57x38x17.5cm)