



SPECIFICATION

- * Drive Space: Three 5.25" ODD bay & Seven 3.5" HDD bay (max. 7 HDD allowed if ATX MB installed)
- * All drive bays equipped with damping function to reduce vibration & extend storage life
- * Equipped with front door by a butterfly security key lock & with removable dust air filter function
- * Screwless hand-free top cover design (screws can also be used & fixed)
- * The main sheet metal constructed by 1.2mm~2.0mm SGCC thickness mechanism
- * Standard with two USB 2.0 ports and LAN/HDD/Power LED at front bezel (two USB 3.0 as option)
- * Standard with one brand new 120mmx25mm intake fan at front
- * Build-in two 80mmx25mm ABS screwless fan brackets at rear panel (fans are option)
- * 8cm or 12cm~14cm fan version standard PS2 PSU compatible (depth at 140mm~260mm)
- * Support SureStar R4S series 400W~500W PS2 Mini Redundant PS (depth 174mm)
- * Support Zippy MRT & MRW series 300W~600W PS2 Mini Redundant PS (depth 185mm)
- * Support SureStar R4B series 600W~800W PS2 Mini Redundant PS (depth 199mm)
- * Support Zippy MRG series 500W~800W PS2 Mini Redundant PS (depth 200mm)
- * Compatible MB: EEB 12"x13", CEB 12"x10.5", ATX 12"x9.6", MicroATX 9.6"x9.6", Mini-ITX 6.7"x6.7"
- * Support 7 full height expansion cards (max. 240mm deep if HDD installed at front)
- * Support 7 full height expansion cards (max. 320mm deep if no HDD installed at front)
- * Standard paint: scratch-resistant black textured at front side of chassis
- * IPC China branded server chassis (with build-in fan) global 3 years warranty
- * Chassis dimension: 19" x 4U x 450mm (17.71" deep)
- * Accessory: MB stand-off x12, #6 round screw x40, M3 truss screw x8, key x2
- * Package: NW 10KGM, GW 12 KGM, 3.19 CUFT (carton size at 62x56x26cm)

