

NSW2020-10T-POE-IN

NSW2020-10T-POE-IN 8PoE+2Port Ethernet Switch UNV



Specifications

Model	NSW2020-10T-POE-IN
Brand	Uniview
Port say?	8 Port
Port sür?ti	100mb/s
PoE	PoE
PoE gücü	100 W

KEY FEATURES

NSW2020-10T-POE-IN

Hardware Specification

Ports Type	10×100Mbps network ports (RJ45), including 8 PoE ports
Prior Ports	1~2
Indicator	POWER Steady on: AC input is normal, POWER Off: No AC input, No PoE Indicator, PoE-MAX off: The POE power supply power of the whole machine is less than 80% of the specification, PoE-MAX Steady on : The POE power supply power of the whole machine is greater than 85% of the specification, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing: Transmitting data
PoE	support POE
Switching capacity	2Gbps
Packet Buffer	448K bit
Max. PoE Power	Max capacity: 88W, Max capacity for single port: 30W
Storage Temperature	-40 °C ~ 70 °C
Working Mode	Default(Normal mode) : All ports can communicate with each other., EXTEND(Surveillance mode): Transmission distance up to 250 meters.
Power Supply	DC: 48/51V, powered by adapter (AC100-240V, 50/60Hz)
Max.Power	94W
Operating humidity	10%~90% (noncondensing)
MAC	1K
Forwarding performance	1.49Mpps
Cooling Fans	0
Weight	0.29KG
Storage humidity	5%~90% (noncondensing)
Dimensions (W×D×H)	171*103*25mm
Operating temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
Standards	IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at