

8Port HDMI KVM Switch

CDHD0800



Feature:

- I. Single USB console control 8 HDMI interface computer and two additional USB device
- II. Supports USB TYPE A interface type keyboard and mouse device
- III. HDMI standard alone KVM resolution in Max: 4K@30HZ
- IV. Switch the computer through the front panel buttons, keyboard hotkeys and screen menu (OSD)
- V. Connect to the controlled device for BIOS-level access without worrying about the risk of viruses and Trojans
- VI. The controlled computer does not need to install any software and drivers, and the controlled computer directly recognizes KVM.
- VII. Upgrade remote network control mode by extending IP board
- VIII. Support OSD to set user login mode and increase KVM login security requirements
- IX. Both local and remote IP modes support high video resolution - support for 480i, 480p, 720p, 1080i and 1080p (1920 × 1200), 4K X 2K Ultra HD resolution

- X. Support widescreen resolution
 - XI. Support DDC communication to adapt to different graphics devices
 - XII. Auto scan function monitors all computer operations
 - XIII. Support for cross-platform operations - Windows, Linux, Mac*, and Sun*
- The computer mouse and mouse connection port is controlled by Keep Online technology to simulate the mouse and keyboard. The device is safe and stable, and the switching is fast without delay.

Specification:

Function		8 Ports	
Computer Connection		8	
Port Selection		OSD Menu, Front panel switches, Hot Key	
Connector	Console Connector	Monitor	1 x HDMI Female
		Keyboard	1 x USB Type A Female
		Mouse	1 x USB Type A Female
	PC Connector	Monitor	8 x HDMI Female
		Mouse/Keyboard	8 x USB TYPE B Female
Power Supply		1 x DC Jack	
Toggle switch	Connection Port Selection		8 x keys
	KVM Switch Reset		1 x Semi-embedded keys
LED Instruction	Selected		8 x Green
	Online		8 x Red
Simulation Method	Keyboard & Mouse		USB
Max Resolution Video		4K@30HZ local	
Scan interval		3、5、10、15、20、30、40、60 seconds (Default 3 Seconds)	
Operating Environment	Operating temperature		0-50℃
	Storage temperature		-20-60℃
	Humidity		0-80%RH, No Condensation
Physical Properties	Housing		metal
	Dimensions(L x W x H)		432 x 155 x 44 mm
	Weight (kgs)		1.8KG