

# RG-NIS3100-8GT2SFP-HP

## True Industrial-Grade Switch Specially Designed for Harsh Environments



### Highlights

- Three Different Models Meet Various Business Scenario Needs
- Unique Industrial Design Ensures Stable Operation in  $-40^{\circ}\text{C}$  to  $80^{\circ}\text{C}$
- 8 KV Protection: The Shield Against Voltage Spike
- IP40 Against 1mm Intruders in Dusty Conditions
- ERPS ensures network stability: service failover within 50ms
- Local Network SON, Easy Configuration even without Cloud

## Highlight Features

RG-NIS3100 Series Industrial Switch

# True Industrial-Grade Specilized for Harsh Environments



## Three Different Models Meet Various Business Scenario Needs



12-56V DC  
Power Supply



STP/ RSTP/  
SNMP/ ERPS<sup>1</sup>



8kV ESD  
Protection



-40°C to +80°C  
Operating Temperature<sup>2</sup>



<sup>1</sup> Release in November 2023  
<sup>2</sup> Installed in a fume hood with a blower, velocity no less than 400 LFM

RG-NIS3100-4GT2SFP-HP  
4 PoE+ 2SFP

RG-NIS3100-8GT2SFP-HP  
8 PoE+ 2SFP

RG-NIS3100-8GT4SFP-HP  
8 PoE+ 4SFP

# Highlight Features

**A Must-Have for Coastal Areas**  
Conquer salt spray corrosion



**Stay Cool, Stay Connected**  
Unique industrial design ensures stable operation in -40°C to 80°C




**8 kV Protection**  
The shield against voltage spike



**Stand Strong in Dusty Environment**  
IP40 Protection: Against 1mm intruders in dusty conditions



**ERPS Plug-and-Play**  
Without complicated configuration



**Local Network SON**  
Easy configuration even without cloud




**Tough Environments, Easy Management**  
Ruijie Cloud: Easy management anytime anywhere



## A Must-Have for Coastal Areas Conquer Salt Spray Corrosion

### 50-um Conformal Coating on PCB Boards

A precisely applied 50-um coating effectively isolates against salt spray, maintaining equipment thermal performance and conductivity.



## Highlight Features



### Enhanced Gold Plating Ports

Gold plating thickness on ports from 3 -um to 15 -um against salt spray corrosion.




### Specialized Outdoor Powder Coating

Preventing equipment surface damage from salt spray erosion.


## Unique Industrial Design Ensures Stable Operation in -40°C to 80°C

Double Heat Dissipation Surface

**126.85%**  
larger surface area




## Highlight Features



## Highlight Features

### Stand Strong in Dusty Environment

**IP40 Protection:**  
Against 1mm intruders in sandstorm conditions



### High kV Protection: The Shield Against Voltage Spike

6kV Surge Protection

8kV ESD Protection<sup>3</sup>



### ERPS Plug-and-Play

Without complicated configuration



## Highlight Features

# LAN Self-Organizing Network

Skip individual configurations, simplify setup



# Ruijie Cloud: Distance No Barrier

Easily manage devices remotely anytime, anywhere



## Product Information

<b>Model</b>	<b>RG-NIS3100-8GT2SFP-HP</b>
<b>Product Category</b>	Layer 2

## Hardware Specifications

<b>Model</b>	<b>RG-NIS3100-8GT2SFP-HP</b>
<b>Product Information</b>	
<b>Warranty</b>	5 years
<b>Port Specifications</b>	
<b>Total number of RJ45 ports</b>	8
<b>Total number of optical ports</b>	2
<b>Number of 1GE combo ports</b>	No
<b>Number of 1GE SFP ports</b>	2
<b>Number of 10GE SFP+ ports</b>	No
<b>Number of 10/100BASE-T ports</b>	No
<b>Number of 10/100/1000BASE-T ports</b>	8
<b>Number of 10/100/1000/2500BASE-T ports</b>	No
<b>Number of 100/1000/2.5G/5G/10GBASE-T ports</b>	No
<b>Module slots</b>	No
<b>Reset button</b>	1
<b>DIP switch</b>	No
<b>Power Supply and Consumption</b>	
<b>PoE Out standard</b>	PoE/PoE+ (IEEE 802.3af/at)
<b>Number of PoE Out ports</b>	8
<b>Number of PoE/PoE+ Out ports</b>	8

# Hardware Specifications

Model	RG-NIS3100-8GT2SFP-HP
Number of PoE/PoE+/PoE++ Out ports	No
PoE budget	240 W
PoE power pins	1-2 (+), 3-6 (-)
Power input	<p>DC power input:</p> <ul style="list-style-type: none"> <li>Rated input voltage: 12 V DC to 56 V DC</li> <li>Maximum input current: 7 A</li> </ul> <p>RG-NIS-PA240-48 (AC input):</p> <ul style="list-style-type: none"> <li>Rated input voltage: 100 V AC to 240 V AC, 50/60 Hz</li> <li>Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz</li> <li>Rated input current: 3.5 A</li> </ul> <p>RG-NIS-PA120-48 (AC input):</p> <ul style="list-style-type: none"> <li>Rated input voltage: 100 V AC to 240 V AC, 50/60 Hz</li> <li>Maximum input voltage: 85 V AC to 264 V AC, 47 Hz to 63 Hz</li> <li>Rated input current: 1.5 A</li> </ul>
Maximum power consumption	<p>20 W (with no PoE load)</p> <p>80 W (full-load power when the input power is 12 V to 20 V)</p> <p>140 W (full-load power when the input power is 21 V to 45 V)</p> <p>260 W (full-load power when the input power is 46 V to 56 V)</p>
Power output	<ul style="list-style-type: none"> <li>RG-NIS-PA240-48</li> </ul> <p>90 V AC to 264 V AC: 54V DC (output voltage), 4.4 A (rated output current)</p> <ul style="list-style-type: none"> <li>RG-NIS-PA120-48</li> </ul> <p>85 V AC to 264 V AC: 48 V DC (output voltage), 2.5 A (rated output current)</p>
Power supply	<ul style="list-style-type: none"> <li>DC power input</li> <li>Power module</li> </ul>
<b>System Specifications</b>	
RAM	256 MB
Flash memory	16 MB
Forwarding rate	14.88 Mpps
Switching capacity	20 Gbps(bit/s)
<b>Dimensions and Weight</b>	
Casing	Metal

# Hardware Specifications

Model	RG-NIS3100-8GT2SFP-HP
Product dimensions (W x D x H)	85 mm x 132 mm x 165 mm (3.35 in. x 5.2 in. x 6.5 in.)
Weight	1.42 kg (3.13 lbs) (without packaging materials)
Shipping weight	1.91 kg (4.21 lbs)
<b>Environment and Reliability</b>	
Hot swapping of fan modules	No
Fan	Fanless design
Cooling	Natural cooling
Acoustic noise	25°C (77°F): 30 dB
Mounting options	DIN rail/Wall
Hot swapping of cables	Service ports support hot swapping of cables.
MTBF	400,000 hours
Operating temperature	-40°C to +65°C (-40°F to 149°F) (installed in a sealed cabinet) -40°C to +70°C (-40°F to 158°F) (installed in a fume hood with a ventilation speed of at least 80LFM (Line Feet Minute)) -40°C to +75°C (-40°F to 167°F) (installed in a fume hood with a ventilation speed of at least 200LFM (Line Feet Minute)) -40°C to +80°C (-40°F to 176°F) (installed in a fume hood with a ventilation speed of at least 400LFM (Line Feet Minute))
Storage temperature	-40°C to +75°C (-40°F to +167°F)
Operating humidity	5% RH to 95% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Altitude	Operating altitude: -500 m to +5,000 m (-1,640.42 ft. to +16,404.20 ft.) Storage altitude: -500 m to +5,000 m (-1,640.42 ft. to +16,404.20 ft.)
Corrosion class	Salt tolerance
ESD protection	Contact discharge: 6 kV Air discharge: 8 kV

# / Hardware Specifications

Model	RG-NIS3100-8GT2SFP-HP
Surge protection	Service port: $\pm 6$ kV for common mode Power connector: $\pm 4$ kV for common mode and $\pm 2$ kV for differential mode
<b>Certification and Regulatory Compliance</b>	
EMC	EN 55032 EN 61000-3-2 EN 61000-3-3 EN 55035 EN 300 386
Safety compliance	IEC 62368-1
Certification	CE, FCC

# Software Specifications

Model	RG-NIS3100-8GT2SFP-HP
<b>Authentication</b>	
<b>RADIUS</b>	Yes
<b>802.1X authentication</b>	Yes
<b>Port-based 802.1X authentication</b>	Yes
<b>MAC address-based 802.1X authentication</b>	Yes
<b>Guest VLAN</b>	Yes
<b>Basic Configurations</b>	
<b>PoE watchdog</b>	Yes
<b>Online upgrade</b>	Yes
<b>Ethernet Switching</b>	
<b>Maximum number of VLANs</b>	4094
<b>Maximum number of MAC address entries</b>	8000
<b>Interface flow control</b>	Yes
<b>MAC address-based VLAN</b>	No
<b>IP subnet - based VLAN assignment</b>	No
<b>IEEE 802.1Q VLAN</b>	Yes
<b>Basic QinQ</b>	No
<b>VLAN configuration supported on LAN ports</b>	Yes
<b>Voice VLAN</b>	Yes
<b>STP (IEEE 802.1d)</b>	Yes
<b>RSTP (IEEE 802.1w)</b>	Yes
<b>MSTP (IEEE 802.1s)</b>	Yes
<b>LLDP</b>	Yes

## Software Specifications

Model	RG-NIS3100-8GT2SFP-HP
LLDP-MED	Yes
Static MAC address	Yes
MAC address filtering	Yes
Static aggregation	Yes
LACP	Yes
Inbound or outbound rate limiting based on interface traffic	Yes
<b>Gateway Features</b>	
802.1p priority-based traffic classification	Yes
DSCP priority-based traffic classification	Yes
Egress queues based on 802.1p and DSCP priorities	Yes
SP	Yes
WRR	Yes
SP+WRR	Yes
Global QoS	Yes
<b>Interface</b>	
Jumbo frame length (MTU)	9216 bytes (global configuration mode)
EEE	Yes
Cable test	Yes
<b>IP Routing</b>	
IPv4 static route	No
IPv6 static route	No
OSPFv2	No
OSPFv3	No

# Software Specifications

Model	RG-NIS3100-8GT2SFP-HP
<b>IP Service</b>	
Maximum number of ARP entries	1000
ARP	Yes
IPv4 ping	Yes
IPv4 traceroute	Yes
IPv6	Yes
ICMPv6	Yes
IPv6 ping	Yes
IPv6 traceroute	Yes
DNS client	Yes
DNSv6 client	Yes
DHCP relay	No
DHCP server	No
DHCP client	Yes
<b>Multicast</b>	
IGMPv1 snooping	Yes
IGMPv2 snooping	Yes
Basic IGMPv3 snooping	Yes
Full IGMPv3 snooping	No
IGMP filtering	Yes
IGMPv1, v2, and v3	No
<b>Network Management and Monitoring</b>	
Port mirroring	Yes
Mirroring	Yes

# Software Specifications

Model	RG-NIS3100-8GT2SFP-HP
HTTP login	Yes
HTTPS login	Yes
RLOG	Yes
SON	Yes
Syslog	Yes
Client auto-discovery	Yes
PoE service failure	Yes
PoE power overload	Yes
SSH	No
Camera detection	Yes
Loop alarm	Yes
MAC address entries	Yes
IP address pool conflicts	Yes
Full ARP table	No
eWeb management	Yes
Ruijie Cloud management	Yes
Ruijie Reyee App management	Yes
SNMPv1, v2c, and v3	Yes
<b>Reliability</b>	
System dual backup	No
Enabling dual backup for the partition Uboot (based on a single flash memory)	No
Load balancing	No
ERPS	Yes

# Software Specifications

Model	RG-NIS3100-8GT2SFP-HP
<b>Security</b>	
<b>Maximum number of ACEs</b>	Number of ACEs in the inbound direction of an interface: 1200 Number of ACEs in the outbound direction of an interface: 0
<b>Port isolation</b>	Yes
<b>Broadcast storm control</b>	Yes
<b>Multicast storm control</b>	Yes
<b>Unknown unicast storm control</b>	Yes
<b>DHCP snooping</b>	Yes
<b>Standard ACL</b>	Yes
<b>Extended MAC ACL</b>	Yes
<b>Extended IP ACL</b>	Yes
<b>IPv6 ACL</b>	Yes
<b>IP-MAC-port binding</b>	Yes
<b>ARP anti-spoofing</b>	Yes
<b>IP source guard</b>	Yes
<b>CPU Protection Policy</b>	Yes
<b>System Performance Capacity</b>	
<b>Recommended camera limit</b>	200 W H265: 80 400 W H265: 40

## Package Contents

<b>Model</b>	<b>RG-NIS3100-8GT2SFP-HP</b>
<b>Device</b>	
<b>Device</b>	1
<b>Accessories</b>	
<b>Rubber pad</b>	No
<b>Power cord retention clip</b>	No
<b>Screw</b>	4 M3 x 6 mm cross recessed countersunk head screws
<b>Grounding cable</b>	No
<b>Power cord</b>	No
<b>Rack-mount bracket</b>	4
<b>Manual</b>	
<b>User Manual</b>	1
<b>Warranty Card</b>	1

*Ruijie* | REYEE

 Redefine your easy network



**Ruijie Networks Co., Ltd.**

Official Website: <https://Reyee.Ruijie.com>